




OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Machine Id
4780

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS

▲ Recommendation

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

▲ Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

▲ Fluid Condition

Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0112553	GFL0093884	GFL0093888
Sample Date	Client Info	21 Mar 2024	22 Oct 2023	07 Oct 2023
Machine Age	hrs	19820	0	19823
Oil Age	hrs	0	0	0
Oil Changed	Client Info	Changed	N/A	N/A
Sample Status		SEVERE	ABNORMAL	SEVERE

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185(m) >100	27	4	8
Chromium	ppm ASTM D5185(m) >20	1	0	<1
Nickel	ppm ASTM D5185(m) >4	<1	0	0
Titanium	ppm ASTM D5185(m)	0	0	0
Silver	ppm ASTM D5185(m) >3	0	<1	<1
Aluminum	ppm ASTM D5185(m) >20	1	1	<1
Lead	ppm ASTM D5185(m) >40	<1	<1	<1
Copper	ppm ASTM D5185(m) >330	1	<1	<1
Tin	ppm ASTM D5185(m) >15	<1	0	0
Antimony	ppm ASTM D5185(m)	0	0	0
Vanadium	ppm ASTM D5185(m)	0	0	0
Beryllium	ppm ASTM D5185(m)	0	0	0
Cadmium	ppm ASTM D5185(m)	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185(m) 2	2	3	7
Barium	ppm ASTM D5185(m) 0	0	<1	<1
Molybdenum	ppm ASTM D5185(m) 50	49	55	50
Manganese	ppm ASTM D5185(m) 0	0	0	0
Magnesium	ppm ASTM D5185(m) 950	786	886	776
Calcium	ppm ASTM D5185(m) 1050	862	976	859
Phosphorus	ppm ASTM D5185(m) 995	786	944	839
Zinc	ppm ASTM D5185(m) 1180	963	1097	968
Sulfur	ppm ASTM D5185(m) 2600	1957	2394	2143
Lithium	ppm ASTM D5185(m)	<1	<1	<1

CONTAMINANTS



method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185(m) >25	5	2	3
Sodium	ppm ASTM D5185(m)	6	3	4
Potassium	ppm ASTM D5185(m) >20	<1	0	0
Fuel	% ASTM D7593* >5	▲ 12.9	▲ 7.9	▲ 9.1

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% ASTM D7844* >3	0.5	0.1	0.1
Nitration	Abs/cm ASTM D7624* >20	11.9	6.4	8.5
Sulfation	Abs/.1mm ASTM D7415* >30	22.5	19.0	22.5



OIL ANALYSIS REPORT











FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	24.0	15.7	23.6

VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	12.00	▲ 9.1	▲ 9.8	▲ 8.7

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0112553
Lab Number : 02624851
Unique Number : 5749970
Test Package : MOB 1 (Additional Tests: PercentFuel)

GFL Environmental - 554 - Edmonton SW
 8409 -15th Street NW
 Edmonton, AB
 CA T6P 0B8
 Contact: Tim Greig
 tgreig@gflenv.com
 T: (780)231-0521
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.