

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id BENCHTANK

Component Bottom Hydraulic System Fluid PETRO CANADA DURATRAN (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.


Fluid Condition


The condition of the oil is acceptable for the time in service.


SAMPLE INFOR	RMATION	M method	limit/base	current	history1	history2
Sample Number		Client Info		PC0040964		
Sample Date		Client Info		06 May 2024		
Machine Age	hrs	Client Info		0		
Dil Age	hrs	Client Info		0		
Dil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINA	TION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR META	LS	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185(m)	>20	1		
Chromium	ppm	ASTM D5185(m)	>10	0		
lickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>10	1		
ead	ppm	ASTM D5185(m)	>10	0		
Copper	ppm	ASTM D5185(m)	>75	0		
īn	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
/anadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	110	99		
Barium	ppm	ASTM D5185(m)	0.0	0		
/lolybdenum	ppm	ASTM D5185(m)	0.0	0		
langanese	ppm	ASTM D5185(m)	1	0		
lagnesium	ppm	ASTM D5185(m)	13	21		
Calcium	ppm	ASTM D5185(m)	3610	3426		
Phosphorus	ppm	ASTM D5185(m)	1192	1079		
Zinc	ppm	ASTM D5185(m)	1455	1344		
Sulfur	ppm	ASTM D5185(m)	2641	2546		
₋ithium	ppm	ASTM D5185(m)		<1		
CONTAMINA	NTS	method	limit/base	current	history1	history2
	NTS ppm	method ASTM D5185(m)	limit/base	current 9	history1	history2
Silicon						
CONTAMINA Silicon Sodium Potassium	ppm	ASTM D5185(m)		9		
Silicon Sodium	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	>20	9 0		
Silicon Sodium Potassium FLUID CLEAN	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	>20 >20	9 0 0		
Silicon Sodium Potassium FLUID CLEAN Particles >4µm	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) S method	>20 >20 limit/base	9 0 0 current	 history1	 history2
Silicon Sodium Potassium FLUID CLEAN Particles >4μm Particles >6μm	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) S method ASTM D7647	>20 >20 limit/base >5000	9 0 0 current 3474	 history1	 history2
Silicon Sodium Potassium	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) Method ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160	9 0 0 current 3474 1017	 history1 	 history2
Silicon Sodium Potassium FLUID CLEAN Particles >4μm Particles >6μm Particles >14μm	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160	9 0 0 current 3474 1017 61	 history1 	 history2
Silicon Sodium Potassium FLUID CLEAN Particles >4μm Particles >6μm Particles >14μm Particles >21μm Particles >38μm	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D7687 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160 >40	9 0 0 current 3474 1017 61 18	 history1 	 history2
Silicon Sodium Potassium FLUID CLEAN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160 >40 >10	9 0 0 current 3474 1017 61 18 3 2 19/17/13	 history1 	 history2




OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
Vhite Metal	scalar	Visual*	NONE	NONE		
ellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Ddor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.1	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
/isc @ 40°C	cSt	ASTM D7279(m)	55.14	55.9		
/isc @ 100°C	cSt	ASTM D7279(m)	9.38	9.4		
/iscosity Index (VI)	Scale	ASTM D2270*	153	151		
SAMPLE IMAG	FS	method	limit/base	current	history1	history2
		monou			- motory -	- Motory2
Color					no image	no image
Bottom					no image	no image
GRAPHS				Particle Count		
GRAPHS Ferrous Alloys			491,520	Particle Count		T ²
Ferrous Alloys			491,520			
Ferrous Alloys			122,880			24
Ferrous Alloys				Į		
Ferrous Alloys			122,880	Į		-24 -27
Ferrous Alloys			122,880	Severe		-2: -2: -2:
Ferrous Alloys			122,880	Severe		-2 -2 -2 -11
Ferrous Alloys	5		122,880	Severe		-2 -2 -2 -11 -11
Ferrous Alloys	5		122,880	Severe		-2 -2 -2 -11 -11
Ferrous Alloys	5		122,880 30,720 129 10 10 10 10 10 10 10 10 10 10 10 10 10	Severe		-2 -2 -11 -11 -11
Ferrous Alloys	5		122.880 30.720 7.680 7.70 1.920 900 480 480 480 1.920 900 480 1.920 1.920 1.920 1.920 1.920 1.920 1.920 1.920 1.920	Severe		-2: -2: -11 -11 -11 -12 -11 -11 -11
Ferrous Alloys	5		122,880 30,720 7,680 7,680 7,680 1,920 9,900 1,920 1,9	Severe		-2 -2 -1 -1 -1 -1 -1
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-2 -2 -1 -1 -1 -1 -1
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe	14μ 21μ	-2: -2: -11 -11 -11 -12 -11 -11 -11
Ferrous Alloys	5		122,880 30,720 7,680 7,680 7,680 1,920 9,900 1,920 1,9	Severe		-24 -22 -18 -18 -14 -12 -12 -12 -12 -12 -12 -12 -12 -12 -12
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-24 -22 -18 -18 -14 -12 -12 -12 -12 -12 -12 -12 -12 -12 -12
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1
Ferrous Alloys	5		122,880 30,720 Te T 30,720 Te	Severe		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1
Ferrous Alloys	5		122,880 30,720 12,980 1,920 1,	Severe		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1



Report Id: BREYOR [WCAMIS] 02634096 (Generated: 05/14/2024 12:19:47) Rev: 1

Contact/Location: Tony Ripa - BREYOR Page 2 of 2