

# **OIL ANALYSIS REPORT**

Sample Rating Trend



#### Machine Id

# JOHN DEERE 245G PL-009 (S/N 1 FT245GXLEE600531)

New (Unused) Oil

Fluid PETRO CANADA ENVIRON MV R 46 (--- GAL)

## DIAGNOSIS

### Recommendation

Il s`agit du relevé de base de cette huile neuve (inutilisée). Le fluide peut servir. (Customer Sample Comment: New oil batch MVR46)

#### Contamination

La propreté du système est acceptable pour votre objectif de propreté ISO 4406. Il n'y a aucun indice de contamination dans le huile (inutilisée) neuve.

### Fluid Condition


Le AN est acceptable pour ce fluide. L'état de l'huile permet d'en l'utilisation.


SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PC0087975		
Sample Date		Client Info		09 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	TION	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		0		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		<1		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	<1	0		
Barium	ppm	ASTM D5185(m)	<1	0		
Molybdenum	ppm	ASTM D5185(m)	<1	0		
Manganese	ppm	ASTM D5185(m)	<1	0		
Magnesium	ppm	ASTM D5185(m)	<1	<1		
Calcium	ppm	ASTM D5185(m)		0		
Phosphorus	ppm	ASTM D5185(m)	626	638		
Zinc	ppm	ASTM D5185(m)		<1		
Sulfur	ppm	ASTM D5185(m)	1236	1370		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINAN	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	0		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*		0		
Nitration	Abs/cm	ASTM D7624*		1.9		
Sulfation	Abs/.1mm	ASTM D7415*		19.4		







# **OIL ANALYSIS REPORT**












FLUID CLEAN	INESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	141		
Particles >6µm		ASTM D7647	>1300	37		
Particles >14µm		ASTM D7647	>160	3		
Particles >21µm		ASTM D7647	>40	1		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	14/12/9		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*		11.3		
Acid Number (AN)	mg KOH/g	ASTM D974*	0.1	0.11		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	43.99	44.0		
Visc @ 100°C	cSt	ASTM D7279(m)	8.17	8.1		
Viscosity Index (VI)	Scale	ASTM D2270*	162	159		
SAMPLE IMAG	FS	method	limit/base	current	historv1	historv2





Report Id: SEM125SAI [WCAMIS] 02638043 (Generated: 05/29/2024 13:49:53) Rev: 1

Submitted By: Vincent Gagne Page 2 of 2