

OIL ANALYSIS REPORT

Area Vessel KAT 05 (BOWTHRUSTER)

Component Bow Thruster Fluid SHELL OMALA 68 (500 LTR)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

		Dec2021	Jul2022 Nov2022	Feb2023 Oct2023 Nov2023	May2024	
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PC0080255	PC0080310	PC0011769
Sample Date		Client Info		17 May 2024	22 Nov 2023	18 Oct 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ATTENTION	NORMAL
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>90	18	17	16
Chromium	ppm	ASTM D5185(m)		0	0	0
Nickel	ppm	ASTM D5185(m)	>10	0	<1	0
Titanium	ppm	ASTM D5185(m)		<1	0	0
Silver	ppm	ASTM D5185(m)		0	<1	<1
Aluminum	ppm	ASTM D5185(m)	>10	<1	<1	0
Lead	ppm	ASTM D5185(m)	>20	0	<1	<1
Copper	ppm	ASTM D5185(m)	>20	<1	<1	<1
Tin	ppm	ASTM D5185(m)	>15	0	0	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		13	14	12
Barium	ppm	ASTM D5185(m)		0	<1	<1
Volybdenum	ppm	ASTM D5185(m)		0	0	0
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)		2	1	<1
Calcium	ppm	ASTM D5185(m)		12	12	11
Phosphorus Zinc	ppm	ASTM D5185(m) ASTM D5185(m)		309 30	291 31	295 28
Sulfur	ppm ppm	ASTM D5185(m) ASTM D5185(m)		30 8102	8343	20 8258
_ithium	ppm	ASTM D5185(m)		<1	<1	<1
CONTAMINAN		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>7	1	3	2
Sodium	ppm	ASTM D5185(m)		10	11	10
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	<1
FLUID CLEANL	INESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	4 37774	6014	
Particles >6µm		ASTM D7647	>1300	<u> </u>	454	
Particles >14µm		ASTM D7647	>160	22	17	
Particles >21µm		ASTM D7647	>40	4	3	
Particles >38µm		ASTM D7647	>10	1	1	
Particles >71µm		ASTM D7647	>3	1	1	
Oil Cleanliness		ISO 4406 (c)	>19/17/14	A 22/19/12	20/16/11	

Sample Rating Trend

Submitted By: Alf Hartery

ISO



🔺 Particle Count

🔺 Particle Trend

144

Jnv8/22

Nov8/22.

Feb7/73

214

38/

Dct18/23

Dct18/23

491,520 122,880

(TEL, 000 (TEL, 30, 720 (TEL, 30, 680 (1, 920) (

120 30

8

40k 35

(m 30k 30k 25k 20k 20k 15k 10k

0

0.60 (B/H0.4

Ê0.36 Ê 0.24 Pio 0.12

0.00

cSt (100°C)

lec27/

Acid Number

lul24/22

Viscosity @ 100°C

Abno 10

> Base Abno

OIL ANALYSIS REPORT

FLUID DEGRAD	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.56	0.50	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	68.0	68.5	68.7	68.7
Visc @ 100°C	cSt	ASTM D7279(m)	8.7	9.0	9.1	9.1
Viscosity Index (VI)	Scale	ASTM D2270*	99	105	107	107
SAMPLE IMAG	ES	method	limit/base	current	history1	history2

Color

.24


22 8


20 4406:1999 Cleanlin 16 14

12 10 8

Bottom

May17/24







Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 CALA : PC0080255 : 28 May 2024 Sample No. Received Lab Number : 02638256 Tested : 30 May 2024 ISO 17025:2017 Accredited Laboratory Diagnosed Unique Number : 5787418 : 30 May 2024 - Wes Davis Test Package : IND 2 (Additional Tests: KV100, TAN Man, VI) To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Ocean Choice International - Katsheshuk II 1315 Topsail Rd, P.O. Box 8190 St. John`s, NL CA A1B 3N4 Contact: Chief Engineer katengine@oceanchoice.com T: F: Submitted By: Alf Hartery

Report Id: KATSHESH [WCAMIS] 02638256 (Generated: 05/30/2024 08:27:59) Rev: 1

Page 2 of 2