

# **OIL ANALYSIS REPORT**

[430339541]

EG-86201

**Unknown Component** 

{not provided} (--- GAL)

# Sample Rating Trend

# **NORMAL**

## DIAGNOSIS

### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.

### Wear

Component wear rates appear to be normal (unconfirmed).

### Contamination

There is no indication of any contamination in the component(unconfirmed).


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.

SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PC0081229		
Sample Date		Client Info		14 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METAL	.S	method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)		8		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		1		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		3		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		<1		
Magnesium	ppm	ASTM D5185(m)		22		
Calcium	ppm	ASTM D5185(m)		5455		
Phosphorus	ppm	ASTM D5185(m)		897		
Zinc	ppm	ASTM D5185(m)		985		
Sulfur	ppm	ASTM D5185(m)		9731		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		4		
Sodium	ppm	ASTM D5185(m)		9		
Potassium	ppm	ASTM D5185(m)	>20	<1		
FLUID DEGRAI		. ,	limit/base			
		ASTM D974*	IIIIII/Dase	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTIVI D9/4"		2.23		



# **OIL ANALYSIS REPORT**







Laboratory Sample No.

Lab Number : 02638296 Unique Number : 5787458

: PC0081229

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Received : 28 May 2024 **Tested** : 29 May 2024

Diagnosed : 29 May 2024 - Kevin Marson Test Package: MAR 2 (Additional Tests: KV100, TAN Man, VI)

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

**Suncor - Terra Nova Projects** 

Scotia Centre, 235 Water Strret St. John's, NL **CA A1C 1B6** 

> Contact: Deanne Badcock dbadcock@suncor.com T: (709)778-3843

F: (709)724-2784