




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
731021
 Component
Natural Gas Engine
 Fluid
CASTROL 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0100769	GFL0100756	GFL0079578
Sample Date	Client Info		26 Jun 2024	05 Dec 2023	24 Jun 2023
Machine Age	kms	Client Info	131353	114513	6056
Oil Age	kms	Client Info	0	0	0
Oil Changed	Client Info		N/A	N/A	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>50	17	11	11
Chromium	ppm	ASTM D5185(m)	>4	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)	>3	0	<1	0
Aluminum	ppm	ASTM D5185(m)	>9	2	2	2
Lead	ppm	ASTM D5185(m)	>30	0	2	7
Copper	ppm	ASTM D5185(m)	>35	1	2	2
Tin	ppm	ASTM D5185(m)	>4	0	<1	<1
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		11	7	6
Barium	ppm	ASTM D5185(m)		3	<1	0
Molybdenum	ppm	ASTM D5185(m)		50	54	54
Manganese	ppm	ASTM D5185(m)		<1	0	<1
Magnesium	ppm	ASTM D5185(m)		528	555	585
Calcium	ppm	ASTM D5185(m)		1536	1672	1590
Phosphorus	ppm	ASTM D5185(m)		668	705	742
Zinc	ppm	ASTM D5185(m)		879	943	943
Sulfur	ppm	ASTM D5185(m)		1980	1981	1941
Lithium	ppm	ASTM D5185(m)		<1	<1	<1

CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>+100	14	4	4
Sodium	ppm	ASTM D5185(m)	>406	5	2	4
Potassium	ppm	ASTM D5185(m)	>20	17	0	<1
Glycol	%	ASTM D7922*		0.0	---	---

INFRA-RED




	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*		0	0	0
Nitration	Abs/cm	ASTM D7624*	>20	10.3	11.9	11.9
Sulfation	Abs/.1mm	ASTM D7415*	>30	19.6	25.3	26.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.0	20.9	21.9











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	14.7	14.9	14.5

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0100769
Lab Number : 02645130
Unique Number : 5802669
Test Package : MOB 1 (Additional Tests: Glycol)

GFL Environmental - 277 - Niagara Regional
 C/O Metro Truck Niagara Inc., 411 Glendale Avenue
 St. Catharines, ON
 CA L2P 3Y1
 Contact: Kelly Bremner
 kbremner@gflenv.com
 T: (437)235-6849
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.