




# OIL ANALYSIS REPORT

## Sample Rating Trend



NORMAL



Machine Id

**215001**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (10 LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0126251</b>	GFL0113271	GFL0097524
Sample Date	Client Info		<b>01 Jul 2024</b>	14 Apr 2024	09 Jan 2024
Machine Age	kms	Client Info	<b>210880</b>	192066	192066
Oil Age	kms	Client Info	<b>9642</b>	0	9442
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>100	<b>17</b>	13	14
Chromium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185(m)	>4	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>3	<b>&lt;1</b>	0	<1
Aluminum	ppm	ASTM D5185(m)	>20	<b>4</b>	3	4
Lead	ppm	ASTM D5185(m)	>40	<b>3</b>	2	3
Copper	ppm	ASTM D5185(m)	>330	<b>1</b>	<1	<1
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	<1
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)	0	<b>3</b>	3	3
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185(m)	60	<b>59</b>	62	59
Manganese	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1	0
Magnesium	ppm	ASTM D5185(m)	1010	<b>944</b>	1011	943
Calcium	ppm	ASTM D5185(m)	1070	<b>1059</b>	1101	1035
Phosphorus	ppm	ASTM D5185(m)	1150	<b>981</b>	1030	983
Zinc	ppm	ASTM D5185(m)	1270	<b>1207</b>	1233	1165
Sulfur	ppm	ASTM D5185(m)	2060	<b>2434</b>	2528	2512
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1

## CONTAMINANTS



	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>25	<b>3</b>	2	3
Sodium	ppm	ASTM D5185(m)		<b>2</b>	2	1
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	<1

## INFRA-RED

	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*	>3	<b>1</b>	0.8	0.8
Nitration	Abs/cm	ASTM D7624*	>20	<b>11.4</b>	11.2	11.3
Sulfation	Abs./1mm	ASTM D7415*	>30	<b>20.9</b>	20.7	21.3



# OIL ANALYSIS REPORT











FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	<b>18.9</b>	19.2	19.8

VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG
Free Water	scalar	Visual*		<b>NEG</b>	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	<b>14.3</b>	14.2	14.4

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0126251 **Received** : 05 Jul 2024  
**Lab Number** : 02645839 **Tested** : 05 Jul 2024  
**Unique Number** : 5803378 **Diagnosed** : 05 Jul 2024 - Wes Davis  
**Test Package** : MOB 1

**GFL Environmental - 216**  
 15 Bermondsey Road  
 Toronto, ON  
 CA M4B 1Y9  
 Contact: Tom Hatzioannidis  
 thatzioannidis@gflenv.com  
 T: (416)678-9340  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.