




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
GFL029
 Machine Id
28
 Component
Diesel Engine
 Fluid
VALVOLINE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			GFL0019845	---	---
Sample Date	Client Info			03 Aug 2021	---	---
Machine Age	hrs Client Info			2384	---	---
Oil Age	hrs Client Info			0	---	---
Oil Changed	Client Info			Not Chngd	---	---
Sample Status				NORMAL	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	---	---
Water	WC Method	>0.2		NEG	---	---
Glycol	WC Method			NEG	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m	>100		6	---	---
Chromium	ppm ASTM D5185m	>20		<1	---	---
Nickel	ppm ASTM D5185m	>4		0	---	---
Titanium	ppm ASTM D5185m			<1	---	---
Silver	ppm ASTM D5185m	>3		<1	---	---
Aluminum	ppm ASTM D5185m	>20		2	---	---
Lead	ppm ASTM D5185m	>40		<1	---	---
Copper	ppm ASTM D5185m	>330		<1	---	---
Tin	ppm ASTM D5185m	>15		<1	---	---
Antimony	ppm ASTM D5185m			0	---	---
Vanadium	ppm ASTM D5185m			<1	---	---
Cadmium	ppm ASTM D5185m			0	---	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m			204	---	---
Barium	ppm ASTM D5185m			0	---	---
Molybdenum	ppm ASTM D5185m			5	---	---
Manganese	ppm ASTM D5185m			<1	---	---
Magnesium	ppm ASTM D5185m			44	---	---
Calcium	ppm ASTM D5185m			2289	---	---
Phosphorus	ppm ASTM D5185m			1022	---	---
Zinc	ppm ASTM D5185m			1171	---	---
Sulfur	ppm ASTM D5185m			3229	---	---




CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m	>25		4	---	---
Sodium	ppm ASTM D5185m			12	---	---
Potassium	ppm ASTM D5185m	>20		14	---	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	>3		0.2	---	---
Nitration	Abs/cm *ASTM D7624	>20		6.5	---	---
Sulfation	Abs/.1mm *ASTM D7415	>30		21.1	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414	>25		16.6	---	---
Base Number (BN)	mg KOH/g ASTM D2896			7.9	---	---











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.5	13.8	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0019845 **Received** : 09 Aug 2021
Lab Number : **05321782** **Tested** : 09 Aug 2021
Unique Number : 9615779 **Diagnosed** : 09 Aug 2021 - Wes Davis
Test Package : MOB1+

GFL Environmental - 9999 - Moved No Longer Used Units

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

US
Contact:

T:
F: