


PROBLEM SUMMARY


Machine Id **225025**


Component **Diesel Engine**

PETRO CANADA DURON SHP 15W40 (--- LTR)



COMPONENT CONDITION SUMMARY





RECOMMENDATION

We advise that you check the fuel injection system. Resample at the next service interval to monitor.

PROBLEMATI	C TEST	Γ RESULT	S		
Sample Status				ABNORMAL	
Fuel	%	ASTM D3524	>5	△ 7.7	
Visc @ 100°C	cSt	ASTM D445	15.4	12.1	

Customer Id: GFL9999 Sample No.: GFL0065560 Lab Number: 05802214 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data: Jonathan Hester +1 919-379-4092 x4092 ihester@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

R		\sim	71	AN.	1F	NI	П	FI	\Box	Δ	\cap	ПΙ	\cap	N	9
	1 = 1		<i>,</i> , , ,	/ I I W	-	IVI			,	\boldsymbol{H}			. ,	ıv	

Action	Status	Date	Done By	Description
Check Fuel/injector System			?	We advise that you check the fuel injection system.

HISTORICAL DIAGNOSIS




OIL ANALYSIS REPORT

Machine Id 225025 Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- L'



DIAGNOSIS

Recommendation

We advise that you check the fuel injection system. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil.


▲ Fluid Condition

Fuel is present in the oil and is lowering the viscosity. The BN result indicates that there is suitable alkalinity remaining in the oil.

.TR)				Mar2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0065560		
Sample Date		Client Info		04 Mar 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				ABNORMAL		
CONTAMINATI	ION	method	limit/base	current	history1	history2
Glycol		WC Method		NEG		
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	26		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	3		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	2		
Boron Barium	ppm ppm	ASTM D5185m ASTM D5185m	0	2 2		
Barium	ppm	ASTM D5185m ASTM D5185m	0	2		
Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m	0 60	2 54		
Barium Molybdenum Manganese	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0	2 54 <1		
Barium Molybdenum Manganese Magnesium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010	2 54 <1 826		
Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010 1070	2 54 <1 826 975		
Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010 1070 1150	2 54 <1 826 975 921		
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010 1070 1150 1270	2 54 <1 826 975 921 1099		
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010 1070 1150 1270 2060	2 54 <1 826 975 921 1099 2653		
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 60 0 1010 1070 1150 1270 2060	2 54 <1 826 975 921 1099 2653	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 60 0 1010 1070 1150 1270 2060	2 54 <1 826 975 921 1099 2653 current	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 60 0 1010 1070 1150 1270 2060 limit/base >25	2 54 <1 826 975 921 1099 2653 current 11	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 60 0 1010 1070 1150 1270 2060 limit/base >25	2 54 <1 826 975 921 1099 2653 current 11 6	 history1	history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 60 0 1010 1070 1150 1270 2060 limit/base >25 >20 >5	2 54 <1 826 975 921 1099 2653 current 11 6 2 7.7	history1	history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel	ppm	ASTM D5185m	0 60 0 1010 1070 1150 1270 2060 limit/base >25 >20 >5	2 54 <1 826 975 921 1099 2653 current 11 6 2 ▲ 7.7	history1	history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844	0 60 0 1010 1070 1150 1270 2060 limit/base >25 >20 >5 limit/base >3	2 54 <1 826 975 921 1099 2653 current 11 6 2 7.7 current 0.9	history1 history1	history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7624	0 60 0 1010 1070 1150 1270 2060 limit/base >25 >20 >5 limit/base	2 54 <1 826 975 921 1099 2653 current 11 6 2 7.7 current 0.9 11.6	history1 history1	history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D3524 method *ASTM D7844 *ASTM D7624 *ASTM D76145	0 60 0 1010 1070 1150 1270 2060 limit/base >25 >20 >5 limit/base >3 >20 >3	2 54 <1 826 975 921 1099 2653 current 11 6 2 7.7 current 0.9 11.6 22.2	history1 history1	history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation FLUID DEGRAG	ppm	ASTM D5185m ASTM D7624 *ASTM D7624 *ASTM D7624 *ASTM D7415 method	0 60 0 1010 1070 1150 1270 2060 limit/base >25 imit/base >3 >20 >30 limit/base	2 54 <1 826 975 921 1099 2653 current 11 6 2 7.7 current 0.9 11.6 22.2 current	history1 history1 history1 history1	history2 history2 history2 history2



OIL ANALYSIS REPORT







Laboratory Sample No. Lab Number **Unique Number**

: GFL0065560 : 05802214 : 10399743

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 27 Mar 2023 Diagnosed

: 30 Mar 2023 Diagnostician : Jonathan Hester **Test Package**: FLEET (Additional Tests: FuelDilution, PercentFuel)

US Contact:

> T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)