




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**921009-559**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.  
NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0078735</b>	GFL0044296	GFL0060743
Sample Date	Client Info	<b>23 Mar 2023</b>	31 Jan 2023	06 Jan 2023
Machine Age	hrs	<b>27146</b>	26751	26751
Oil Age	hrs	<b>560</b>	1	1300
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>27</b>	12	▲ 83
Chromium	ppm ASTM D5185m >20	<b>1</b>	<1	3
Nickel	ppm ASTM D5185m >4	<b>0</b>	<1	<1
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	3
Lead	ppm ASTM D5185m >40	<b>0</b>	1	4
Copper	ppm ASTM D5185m >330	<b>&lt;1</b>	<1	2
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>2</b>	4	3
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>53</b>	62	62
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>956</b>	1003	919
Calcium	ppm ASTM D5185m 1070	<b>1138</b>	1179	1141
Phosphorus	ppm ASTM D5185m 1150	<b>938</b>	1068	959
Zinc	ppm ASTM D5185m 1270	<b>1334</b>	1420	1252
Sulfur	ppm ASTM D5185m 2060	<b>2963</b>	4027	3117

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>6</b>	4	11
Sodium	ppm ASTM D5185m	<b>10</b>	3	11
Potassium	ppm ASTM D5185m >20	<b>4</b>	3	3

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.7</b>	0.3	1.8
Nitration	Abs/cm *ASTM D7624 >20	<b>8.8</b>	5.6	13.6
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.1</b>	18.1	26.5

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.8</b>	13.4	22.6
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.8</b>	9.0	7.5







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.3</b>	14.1	14.1

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0078735 **Received** : 29 Mar 2023  
**Lab Number** : **05804918** **Diagnosed** : 30 Mar 2023  
**Unique Number** : 10402447 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 622 - Traverse City Hauling**  
 160 Hughes Dr  
 Traverse City, MI  
 US 49686  
 Contact: GARY BREWER

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)