

# **OIL ANALYSIS REPORT**

Sample Rating Trend







# Machine Id **12023**

Component **Diesel Engine** 

PETRO CANADA DURON SHP 15W40 (10 GAL)

# DIAGNOSIS

## Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil


## **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0077268	PCA0077337	PCA0077309
Sample Date		Client Info		24 May 2023	13 Mar 2023	21 Dec 2022
Machine Age	hrs	Client Info		8749	8278	7715
Oil Age	hrs	Client Info		471	0	480
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	8	11	11
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	2	2	1
Lead	ppm	ASTM D5185m	>40	1	0	0
Copper	ppm	ASTM D5185m	>330	0	<1	1
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
				-		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base		history1	history2
				current		
Boron	ppm	ASTM D5185m	0	current	10	19
Boron Barium	ppm ppm	ASTM D5185m ASTM D5185m	0	current 18 0	10 <1	19 0
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60	current 18 0 72	10 <1 60	19 0 65
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0	current 18 0 72 <1	10 <1 60 <1	19 0 65 <1
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0 1010	current  18  0  72  <1  906	10 <1 60 <1 839	19 0 65 <1 729
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0 1010 1070	current  18  0  72  <1  906  1263	10 <1 60 <1 839 1131	19 0 65 <1 729 1369 934 1133
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060	current  18  0  72  <1  906  1263  1031	10 <1 60 <1 839 1131 917	19 0 65 <1 729 1369 934
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060	current  18 0 72 <1 906 1263 1031 1283 3577 current	10 <1 60 <1 839 1131 917 1209 3456 history1	19 0 65 <1 729 1369 934 1133 3414 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060	current  18  0  72  <1  906  1263  1031  1283  3577  current  4	10 <1 60 <1 839 1131 917 1209 3456 history1	19 0 65 <1 729 1369 934 1133 3414 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm	ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060 limit/base	current  18  0  72  <1  906  1263  1031  1283  3577  current  4	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2	19 0 65 <1 729 1369 934 1133 3414 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060 limit/base	current  18  0  72  <1  906  1263  1031  1283  3577  current  4	10 <1 60 <1 839 1131 917 1209 3456 history1	19 0 65 <1 729 1369 934 1133 3414 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060 limit/base	current  18  0  72  <1  906  1263  1031  1283  3577  current  4	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2	19 0 65 <1 729 1369 934 1133 3414 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm	ASTM D5185m	0 0 60 0 1010 1070 1150 1270 2060 limit/base >25	current  18  0  72  <1  906  1263  1031  1283  3577  current  4  4	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2	19 0 65 <1 729 1369 934 1133 3414 history2 3 4
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	0 0 0 0 1010 1070 1150 1270 2060 limit/base >25 >20 limit/base	current  18  0  72  <1  906  1263  1031  1283  3577  current  4  2  current	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2 0 history1 0.5 8.2	19 0 65 <1 729 1369 934 1133 3414 history2 3 4 2 history2 0.6 8.9
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  Method  *ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 0 60 0 1010 1150 1270 2060 limit/base >25 >20 limit/base	current  18  0  72  <1  906  1263  1031  1283  3577  current  4  2  current  0.4	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2 0 history1 0.5	19 0 65 <1 729 1369 934 1133 3414 history2 3 4 2 history2 0.6
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm	ASTM D5185m  Method ASTM D5185m ASTM D76185m  Method *ASTM D7844 *ASTM D7624 *ASTM D76145	0 0 60 0 1010 1150 1270 2060 limit/base >25 >20 limit/base	current  18 0 72 <1 906 1263 1031 1283 3577 current 4 4 2 current 0.4 6.5	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2 0 history1 0.5 8.2	19 0 65 <1 729 1369 934 1133 3414 history2 3 4 2 history2 0.6 8.9
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm	ASTM D5185m  Method ASTM D5185m ASTM D76185m  Method *ASTM D7844 *ASTM D7624 *ASTM D76145	0 0 0 0 1010 1070 1150 1270 2060 limit/base >25 >20 limit/base >3 >20 >30	current  18  0  72  <1  906  1263  1031  1283  3577  current  4  4  2  current  0.4  6.5  18.7	10 <1 60 <1 839 1131 917 1209 3456 history1 3 2 0 history1 0.5 8.2 19.3	19 0 65 <1 729 1369 934 1133 3414 history2 3 4 2 history2 0.6 8.9 20.5



# **OIL ANALYSIS REPORT**








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	RTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	12.8	13.5

## **GRAPHS**













Certificate L2367

Laboratory Sample No.

Lab Number **Unique Number** Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : PCA0077268 : 05858951 : 10493416

Received Diagnosed Diagnostician : Wes Davis

: 30 May 2023 : 30 May 2023

GFL Environmental - 002 - Vance-Granville

241 Vanco Mill Rd Henderson, NC US 27537

Contact: Cameron King cameron.king@gflenv.com

T: (252)438-5333 F: (252)431-1635

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)