


OIL ANALYSIS REPORT



Machine Id
CATERPILLAR BASIN DRILLING 103
 Component
3 Diesel Engine
 Fluid
CHEVRON URSA SUPER PLUS EC 15W40 (--- GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.
 NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0096202	PCA0096219	PCA0093225
Sample Date	Client Info		25 May 2023	26 Apr 2023	27 Mar 2023
Machine Age	hrs	Client Info	0	0	0
Oil Age	hrs	Client Info	0	0	0
Oil Changed		Client Info	N/A	N/A	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	6	7	4
Chromium	ppm	ASTM D5185m >20	0	<1	<1
Nickel	ppm	ASTM D5185m >2	0	0	0
Titanium	ppm	ASTM D5185m >2	0	0	0
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >25	<1	0	2
Lead	ppm	ASTM D5185m >40	2	2	<1
Copper	ppm	ASTM D5185m >330	11	11	10
Tin	ppm	ASTM D5185m >15	<1	<1	0
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	209	280	291
Barium	ppm	ASTM D5185m	0	0	0
Molybdenum	ppm	ASTM D5185m	102	104	100
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m	465	486	477
Calcium	ppm	ASTM D5185m	1420	1417	1474
Phosphorus	ppm	ASTM D5185m 1200	896	979	916
Zinc	ppm	ASTM D5185m 1300	1110	1192	1157
Sulfur	ppm	ASTM D5185m	2830	3076	3510

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	6	9	6
Sodium	ppm	ASTM D5185m	4	6	4
Potassium	ppm	ASTM D5185m >20	3	3	2




INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	8.9	7.7	7.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	24.1	21.5	22.6

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	19.4	17.8	16.9
Base Number (BN)	mg KOH/g	ASTM D2896 8.0	7.57	6.37	6.81





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.0	13.0

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0096202 **Received** : 05 Jun 2023
Lab Number : **05864518** **Tested** : 06 Jun 2023
Unique Number : 10498983 **Diagnosed** : 06 Jun 2023 - Wes Davis
Test Package : IND 2

DELTA FUEL COMPANY
 1000 WELLS ISLAND RD
 SHREVEPORT, LA
 US 71107
 Contact: BRAD GORDON
 bgordon@deltafuel.com
 T: (318)780-3921
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)