




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**[415568]**  
 Machine Id  
**420089 - SW4012**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history 1	history 2
Sample Number	Client Info	<b>GFL0083424</b>	GFL0065135	---
Sample Date	Client Info	<b>06 Jun 2023</b>	30 Mar 2023	---
Machine Age	hrs Client Info	<b>9898</b>	9561	---
Oil Age	hrs Client Info	<b>0</b>	0	---
Oil Changed	Client Info	<b>Changed</b>	Changed	---
Sample Status		<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

method	limit/base	current	history 1	history 2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	---
Glycol	WC Method	<b>NEG</b>	NEG	---

## WEAR METALS

method	limit/base	current	history 1	history 2
Iron	ppm ASTM D5185m >80	<b>3</b>	14	---
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	1	---
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	---
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	---
Silver	ppm ASTM D5185m >3	<b>0</b>	0	---
Aluminum	ppm ASTM D5185m >30	<b>0</b>	6	---
Lead	ppm ASTM D5185m >30	<b>&lt;1</b>	0	---
Copper	ppm ASTM D5185m >150	<b>1</b>	4	---
Tin	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	---
Vanadium	ppm ASTM D5185m	<b>0</b>	0	---
Cadmium	ppm ASTM D5185m	<b>&lt;1</b>	0	---

## ADDITIVES

method	limit/base	current	history 1	history 2
Boron	ppm ASTM D5185m 0	<b>&lt;1</b>	2	---
Barium	ppm ASTM D5185m 0	<b>&lt;1</b>	0	---
Molybdenum	ppm ASTM D5185m 60	<b>59</b>	63	---
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	---
Magnesium	ppm ASTM D5185m 1010	<b>969</b>	971	---
Calcium	ppm ASTM D5185m 1070	<b>1067</b>	1137	---
Phosphorus	ppm ASTM D5185m 1150	<b>1029</b>	1031	---
Zinc	ppm ASTM D5185m 1270	<b>1261</b>	1308	---
Sulfur	ppm ASTM D5185m 2060	<b>3758</b>	3352	---

## CONTAMINANTS

method	limit/base	current	history 1	history 2
Silicon	ppm ASTM D5185m >20	<b>3</b>	3	---
Sodium	ppm ASTM D5185m	<b>3</b>	2	---
Potassium	ppm ASTM D5185m >20	<b>3</b>	11	---

## INFRA-RED



method	limit/base	current	history 1	history 2
Soot %	% *ASTM D7844 >3	<b>0.1</b>	0.4	---
Nitration	Abs/cm *ASTM D7624 >20	<b>5.1</b>	9.1	---
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>18.1</b>	22.3	---

## FLUID DEGRADATION

method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.7</b>	17.8	---
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>9.9</b>	9.1	---







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history 1	history 2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history 1	history 2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.6</b>	14.9	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0083424 **Received** : 28 Jun 2023  
**Lab Number** : 05885375 **Diagnosed** : 30 Jun 2023  
**Unique Number** : 10535858 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 983 - Sugar Land Hauling**  
 16011 West Belfort Street  
 Sugar Land, TX  
 US 77498  
 Contact: Gino Griego  
 ggriego@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: