




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**428015-901**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history 1	history 2
Sample Number	Client Info		<b>GFL0062189</b>	GFL0062242	GFL0043664
Sample Date	Client Info		<b>26 Jun 2023</b>	20 Feb 2023	14 Sep 2022
Machine Age	hrs	Client Info	<b>17024</b>	16850	16593
Oil Age	hrs	Client Info	<b>195</b>	257	600
Oil Changed	Client Info		<b>Not Chngd</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history 1	history 2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m >100	<b>5</b>	11	16
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	0	1
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	<1	3
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	2
Copper	ppm	ASTM D5185m >330	<b>1</b>	0	1
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

	method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185m 0	<b>9</b>	4	5
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	3
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	59	55
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>928</b>	883	805
Calcium	ppm	ASTM D5185m 1070	<b>1118</b>	1119	1063
Phosphorus	ppm	ASTM D5185m 1150	<b>1031</b>	941	923
Zinc	ppm	ASTM D5185m 1270	<b>1261</b>	1164	1116
Sulfur	ppm	ASTM D5185m 2060	<b>3744</b>	3101	3086

## CONTAMINANTS

	method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185m >25	<b>2</b>	4	3
Sodium	ppm	ASTM D5185m	<b>9</b>	13	22
Potassium	ppm	ASTM D5185m >20	<b>1</b>	3	7

## INFRA-RED



	method	limit/base	current	history 1	history 2
Soot %	%	*ASTM D7844 >3	<b>0.2</b>	0.2	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>6.5</b>	7.7	9.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.6</b>	18.5	20.6

## FLUID DEGRADATION

	method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.4</b>	14.8	16.6
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.8</b>	8.8	10.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history 1	history 2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history 1	history 2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.4</b>	13.1	13.7

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0062189 **Received** : 29 Jun 2023  
**Lab Number** : **05886464** **Diagnosed** : 02 Jul 2023  
**Unique Number** : 10536947 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 626 - Cadillac Hauling**  
 1501 Ron Wilson St  
 Cadillac, MI  
 US 49601  
 Contact: GARY BREWER  
 gbrewerjr@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: