


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **427127-275**

Component

Diesel Engine

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)		Feb2022	Aug2022	Jan 2023 Apr 2023	Jun2023	
SAMPLE INFOR	MATION	method	limit/base	current	history 1	history 2
Sample Number		Client Info		GFL0087807	GFL0074921	GFL0070577
Sample Date		Client Info		27 Jun 2023	10 Apr 2023	26 Jan 2023
Machine Age	mls	Client Info		235087	25199	6597
Oil Age	mls	Client Info		235087	200	600
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history 1	history 2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m	>100	7	4	23
Chromium	ppm	ASTM D5185m	>20	0	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	1	4
Lead	ppm	ASTM D5185m	>40	<1	0	1
Copper	ppm	ASTM D5185m	>330	1	<1	4
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185m	0	44	30	260
Barium	ppm	ASTM D5185m	0	2	0	0
Molybdenum	ppm	ASTM D5185m	60	69	57	106
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	795	717	624
Calcium	ppm	ASTM D5185m	1070	1117	1048	1299
Phosphorus	ppm	ASTM D5185m	1150	991	900	724
Zinc	ppm	ASTM D5185m	1270	1111	1087	848
Sulfur	ppm	ASTM D5185m	2060	3026	3401	2971
CONTAMINAN	ITS	method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185m	>25	3	4	8
Sodium	ppm	ASTM D5185m		0	1	8
Potassium	ppm	ASTM D5185m	>20	2	2	0
INFRA-RED		method	limit/base	current	history 1	history 2
Soot %	%	*ASTM D7844	>3	0.5	0.5	1.1
Nitration	Abs/cm	*ASTM D7624	>20	6.2	5.5	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.1	16.8	23.2
FLUID DEGRA	DATION	method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.3	13.2	16.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	9.3	8.5	9.1



18

OIL ANALYSIS REPORT





Jun27/23	Silt	scalar			
	Debris	scalar			
	Sand/Dirt	scalar			
	Appearance	scalar			
- I	Odor	scalar			
	Emulsified Water	scalar			
	Free Water	scalar			
	FLUID PROPERTIES				
	Visc @ 100°C	cSt			
	GRAPHS				
	Ferrous Alloys				


VISUAL		method	limit/base	current	history 1	history 2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROP	EKIIES	method	ilmit/base		nistory i	nistory 2
Visc @ 100°C	cSt	ASTM D445	15.4	14.2	14.1	13.3

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Test Package : FLEET

Unique Number : 10539251

: GFL0087807 : 05888768

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 03 Jul 2023 Diagnosed : 05 Jul 2023

Diagnostician : Wes Davis

GFL Environmental - 166 - Phenix City

18 Old Brickyard Rd Phenix City, AL US 36869

Contact: DEAN PEACE JR dean.peace@gflenv.com

T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: