	ARY Sample Rating Trend	VIS DEBRIS
Machine Id 2026886		
Component Rear Differential		
GEAR OIL SAE 75W90 (QTS)	Jun ¹ 223	

No relevant graphs to display

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

PROBLEMATIO	C TEST	RESULT	S		
Sample Status				ABNORMAL	
Debris	scalar	*Visual	NONE	A MODER	

Customer Id: PERLEWNC Sample No.: PCA0099029 Lab Number: 05889462 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data: Sean Felton +1 919-379-4092 sfelton@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u> There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 2026886

Component **Rear Differential** Fluid GEAR OIL SAE 75W90 (--- QTS)

DIAGNOSIS

A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history 1	history 2
Sample Number		Client Info		PCA0099029		
Sample Date		Client Info		29 Jun 2023		
Machine Age	mls	Client Info		214231		
Oil Age	mls	Client Info		214231		
Oil Changed		Client Info		Not Changd		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m	>500	132		
Chromium	ppm	ASTM D5185m	>10	1		
Nickel	ppm	ASTM D5185m	>10	5		
	ppm	ASTM D5185m		0		
	ppm	ASTM D5185m		0		
	ppm	ASTM D5185m	>25	1		
	ppm	ASTM D5185m	>25	0		
	ppm	ASTM D5185m	>100	2		
	ppm	ASTM D5185m	>10	- <1		
	ppm	ASTM D5185m		0		
	ppm	ASTM D5185m		0		
	ppin			-		
ADDITIVES		method	limit/base	current	history 1	history 2
	ppm	ASTM D5185m	400	299		
Barium	ppm	ASTM D5185m	200	2		
Molybdenum	ppm	ASTM D5185m	12	0		
Manganese	ppm	ASTM D5185m		12		
Magnesium	ppm	ASTM D5185m	12	<1		
Calcium	ppm	ASTM D5185m	150	11		
Phosphorus	ppm	ASTM D5185m	1650	1412		
Zinc	ppm	ASTM D5185m	125	7		
Sulfur	ppm	ASTM D5185m	22500	28438		
CONTAMINANT	S	method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185m	>75	24		
Sodium	ppm	ASTM D5185m		7		
Potassium	ppm	ASTM D5185m	>20	2		
VISUAL		method	limit/base	current	history 1	history 2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE			
Sand/Dirt s	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
	scalar	*Visual	>.2	NEG		
	scalar	*Visual		NEG		
FLUID PROPER	TIES	method	limit/base	current	history 1	history 2
	cSt	ASTM D445	109	106		
7:05:04) Rev: 1		, 10 1 10 170			SON WALLACE	- PERLEWNC
			Sonia			

Report Id: PERLEWNC [WUSCAR] 05889462 (Generated: 07/06/2023 17:05:04) Rev: 1



OIL ANALYSIS REPORT



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)