

# **OIL ANALYSIS REPORT**

#### Sample Rating Trend







Machine Id 630781

Component Diesel Engine Fluid

PETRO CANADA DURON SHP 10W30 (--- GAL)

# DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

Metal levels are typical for a components first oil change.

### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

## Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORI	MATION	method	limit/base	current	history 1	history 2
Sample Number		Client Info		PCA0100770		
Sample Date		Client Info		21 Jun 2023		
Machine Age	mls	Client Info		46875		
Oil Age	mls	Client Info		46875		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history 1	history 2
Fuel		WC Method	>5	<1.0		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m	>100	99		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>4	<1		
Titanium	ppm	ASTM D5185m		2		
Silver	ppm	ASTM D5185m	>3	<1		
Aluminum	ppm	ASTM D5185m	>20	35		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	46		
Tin	ppm	ASTM D5185m	>15	3		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history 1	history 2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 18	history 1	history 2
	ppm ppm					
Boron		ASTM D5185m	2	18		
Boron Barium	ppm	ASTM D5185m ASTM D5185m	2 0	18 <1		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50	18 <1 18		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0	18 <1 18 4		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950	18 <1 18 4 832		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050	18 <1 18 4 832 1438	   	   
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995	18 <1 18 4 832 1438 797	   	   
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180	18 <1 18 4 832 1438 797 1021		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600	18 <1 18 4 832 1438 797 1021 3503		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600	18 <1 18 4 832 1438 797 1021 3503 current		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600	18 <1 18 4 832 1438 797 1021 3503 current 16	    history 1	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m <b>method</b> ASTM D5185m	2 0 50 950 1050 995 1180 2600 <b>imit/base</b> >25	18 <1 18 4 832 1438 797 1021 3503 <u>current</u> 16 6	     history 1 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>imit/base</b> >25 >20	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85	    history 1  	     history 2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>imit/base</b> >25 -20 <b>imit/base</b>	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85 current	     history 1   history 1	     history 2   history 2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>limit/base</b> >25 >20 <b>limit/base</b>	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85 current 0.6	     history 1   history 1  history 1	     history 2  history 2 
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>imit/base</b> >25 >20 <b>imit/base</b> >3 >20	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85 current 0.6 13.6	      history 1    history 1  	     history 2   history 2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 imit/base >25 >20 imit/base >3 >20 >30	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85 current 0.6 13.6 27.1	     history 1  history 1  history 1	    history 2  history 2  history 2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7844	2 0 50 0 950 1050 995 1180 2600 imit/base >25 >20 imit/base >3 >20 >30	18 <1 18 4 832 1438 797 1021 3503 current 16 6 85 current 0.6 13.6 27.1 current	     history 1   history 1  history 1  history 1	    history 2  history 2  history 2  history 2 



14

cSt (100°C)

Abnorm

# **OIL ANALYSIS REPORT**

scalar

scalar

scalar

\*Visual

\*Visual

\*Visual

scalar \*Visual

NONE

NONE

NONE

NONE

NONE

NONE

NONE

NONE


VISUAL

White Metal

Yellow Metal

Precipitate

Silt





Contact/Location: JOHN KEEN - MILPHINE