




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id

14

Component

Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history 1	history 2
Sample Number	Client Info		GFL0067706	GFL0067818	GFL0067743
Sample Date	Client Info		06 Jul 2023	27 Apr 2023	04 Apr 2023
Machine Age	mls	Client Info	0	0	232347
Oil Age	mls	Client Info	0	0	0
Oil Changed	Client Info		N/A	Not Changd	Not Changd
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history 1	history 2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m >100	83	68	69
Chromium	ppm	ASTM D5185m >20	3	3	3
Nickel	ppm	ASTM D5185m >4	1	2	<1
Titanium	ppm	ASTM D5185m	<1	<1	<1
Silver	ppm	ASTM D5185m >3	0	<1	0
Aluminum	ppm	ASTM D5185m >20	6	4	6
Lead	ppm	ASTM D5185m >40	<1	1	0
Copper	ppm	ASTM D5185m >330	3	2	2
Tin	ppm	ASTM D5185m >15	1	2	<1
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185m 250	4	4	4
Barium	ppm	ASTM D5185m 10	0	0	0
Molybdenum	ppm	ASTM D5185m 100	66	57	62
Manganese	ppm	ASTM D5185m	1	<1	1
Magnesium	ppm	ASTM D5185m 450	1027	924	917
Calcium	ppm	ASTM D5185m 3000	1292	1165	1219
Phosphorus	ppm	ASTM D5185m 1150	1157	1051	1033
Zinc	ppm	ASTM D5185m 1350	1468	1349	1353
Sulfur	ppm	ASTM D5185m 4250	3683	3419	3125

CONTAMINANTS

	method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185m >25	17	16	17
Sodium	ppm	ASTM D5185m >158	23	20	21
Potassium	ppm	ASTM D5185m >20	7	7	4

INFRA-RED



	method	limit/base	current	history 1	history 2
Soot %	%	*ASTM D7844 >3	0.8	0.8	0.8
Nitration	Abs/cm	*ASTM D7624 >20	14.0	11.9	11.6
Sulfation	Abs/.1mm	*ASTM D7415 >30	25.9	22.9	21.7

FLUID DEGRADATION

	method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm	*ASTM D7414 >25	24.7	22.3	20.7
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	8.2	6.7	6.7







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history 1	history 2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history 1	history 2
Visc @ 100°C	cSt	ASTM D445	14.4	15.0	14.5

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0067706 **Received** : 07 Jul 2023
Lab Number : 05892068 **Diagnosed** : 09 Jul 2023
Unique Number : 10547878 **Diagnostician** : Doug Bogart
Test Package : FLEET

GFL Environmental - 840 - Kansas City East
 212 East Broadway Street
 Grain Valley, MO
 US 64029
 Contact: CHRIS GILKEY
 CGILKEY@GFLENV.COM
 T:
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)