

OIL ANALYSIS REPORT




{UNASSIGNED} 933041

Component

Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (8 GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

| SAMPLE INFOR | MATION | method | limit/base | current | history 1 | history 2 |
|----------------------|-------------|-------------|------------|-------------|-------------|-----------|
| Sample Number | | Client Info | | GFL0086128 | GFL0083232 | |
| Sample Date | | Client Info | | 06 Jul 2023 | 15 Jun 2023 | |
| Machine Age | hrs | Client Info | | 391 | 216 | |
| Oil Age | hrs | Client Info | | 391 | 216 | |
| Oil Changed | | Client Info | | Not Changd | Not Changd | |
| Sample Status | | | | NORMAL | NORMAL | |
| WEAR METAL | S | method | limit/base | current | history 1 | history 2 |
| Iron | ppm | ASTM D5185m | >235 | 33 | 27 | |
| Chromium | ppm | ASTM D5185m | | 0 | 0 | |
| Nickel | ppm | ASTM D5185m | >2 | <1 | 0 | |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | |
| Silver | ppm | ASTM D5185m | >5 | <1 | 0 | |
| Aluminum | ppm | ASTM D5185m | | 4 | 3 | |
| Lead | ppm | ASTM D5185m | >45 | <1 | <1 | |
| Copper | ppm | ASTM D5185m | | 7 | 5 | |
| Coppei Tin | ppm | | >10 | <1 | <1 | |
| Vanadium | ppm | ASTM D5185m | >10 | 0 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| ADDITIVES | le le · · · | method | limit/base | current | history 1 | history 2 |
| Boron | nnm | ASTM D5185m | mmobase | 67 | 62 | |
| Barium | ppm | ASTM D5185m | | <1 | 3 | |
| Molybdenum | ppm | ASTM D5185m | | <1 | <1 | |
| • | ppm | ASTM D5185m | | 1 | <1 | |
| Manganese | ppm | ASTM D5185m | | 1 | <1 | |
| Magnesium Calcium | ppm | ASTM D5185m | | 128 | 126 | |
| | ppm | ASTM D5185m | | 204 | 208 | |
| Phosphorus | ppm | | | 19 | | |
| Zinc | ppm | ASTM D5185m | | | 16 | |
| Sulfur | ppm | ASTM D5185m | | 1667 | 1874 | |
| CONTAMINAN | IIS | method | limit/base | current | history 1 | history 2 |
| Silicon | ppm | | >20 | 4 | 4 | |
| Sodium | ppm | ASTM D5185m | | 0 | 2 | |
| Potassium | ppm | ASTM D5185m | >20 | 4 | 3 | |
| VISUAL | | method | limit/base | current | history 1 | history 2 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | |
| Silt | scalar | *Visual | NONE | NONE | NONE | |
| Debris | scalar | *Visual | NONE | NONE | NONE | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | |
| Appearance | scalar | *Visual | NORML | NORML | NORML | |
| Odor | scalar | *Visual | NORML | NORML | NORML | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | |
| Free Water | scalar | *Visual | | NEG | NEG | |
| FLUID PROPE | RTIES | method | limit/base | current | history 1 | history 2 |
| Vies @ 40°C | - 04 | ACTM DAAF | 0.4 | 22.0 | 22.2 | |




OIL ANALYSIS REPORT







GRAPHS



Non-ferrous Metals



Viscosity @ 40°C







Laboratory Sample No. Lab Number Unique Number : 10549916

: 05894106 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 10 Jul 2023 : GFL0086128 Received Diagnosed : 12 Jul 2023

Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge 1280 Rum Creek Parkway

Stockbridge, GA US 30281

Contact: JOSHUA TINKER joshuatinker@gflenv.com

T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)