

# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**


Area  
**(AU703W) Supermarket [182637]**  
 Machine Id  
**FREIGHTLINER 107A1887**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**


**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor.

**Wear**

Metal levels are typical for a components first oil change.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

**SAMPLE INFORMATION**

	method	limit/base	current	history 1	history 2
Sample Number	Client Info		<b>PCA0100429</b>	---	---
Sample Date	Client Info		<b>28 Jun 2023</b>	---	---
Machine Age	mls	Client Info	<b>208719</b>	---	---
Oil Age	mls	Client Info	<b>208719</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

**CONTAMINATION**

	method	limit/base	current	history 1	history 2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

**WEAR METALS**

	method	limit/base	current	history 1	history 2
Iron	ppm	ASTM D5185m >80	<b>13</b>	---	---
Chromium	ppm	ASTM D5185m >5	<b>1</b>	---	---
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185m	<b>0</b>	---	---
Silver	ppm	ASTM D5185m >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m >30	<b>9</b>	---	---
Lead	ppm	ASTM D5185m >30	<b>0</b>	---	---
Copper	ppm	ASTM D5185m >150	<b>5</b>	---	---
Tin	ppm	ASTM D5185m >5	<b>&lt;1</b>	---	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	---	---

**ADDITIVES**

	method	limit/base	current	history 1	history 2
Boron	ppm	ASTM D5185m 2	<b>5</b>	---	---
Barium	ppm	ASTM D5185m 0	<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185m 50	<b>59</b>	---	---
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	---	---
Magnesium	ppm	ASTM D5185m 950	<b>952</b>	---	---
Calcium	ppm	ASTM D5185m 1050	<b>1154</b>	---	---
Phosphorus	ppm	ASTM D5185m 995	<b>1074</b>	---	---
Zinc	ppm	ASTM D5185m 1180	<b>1357</b>	---	---
Sulfur	ppm	ASTM D5185m 2600	<b>3675</b>	---	---

**CONTAMINANTS**

	method	limit/base	current	history 1	history 2
Silicon	ppm	ASTM D5185m >20	<b>4</b>	---	---
Sodium	ppm	ASTM D5185m	<b>2</b>	---	---
Potassium	ppm	ASTM D5185m >20	<b>6</b>	---	---



**INFRA-RED**

	method	limit/base	current	history 1	history 2
Soot %	%	*ASTM D7844 >3	<b>0.6</b>	---	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.7</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.2</b>	---	---

**FLUID DEGRADATION**

	method	limit/base	current	history 1	history 2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.9</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>6.9</b>	---	---





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history 1	history 2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history 1	history 2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	---	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0100429 **Received** : 10 Jul 2023  
**Lab Number** : 05894333 **Diagnosed** : 11 Jul 2023  
**Unique Number** : 10550143 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1072 - Supermarket-Elizabeth**  
 505 Division Street  
 Elizabeth, NJ  
 US 07207  
 Contact: Normand Brizak  
 nbrizak@transervice.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: