

OIL ANALYSIS REPORT

Sample Rating Trend









428060-402359

Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

14 3111 13W 40 (GAL)	Feb 2019	Dec2019 Mar2022	Jan2023 May2023	Jul2023	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0067732	GFL0067681	GFL0067674
Sample Date		Client Info		07 Jul 2023	06 Jun 2023	18 May 2023
Machine Age	mls	Client Info		0	0	0
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>120	5	4	3
Chromium	ppm	ASTM D5185m	>20	<1	<1	0
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	0	0
_ead	ppm	ASTM D5185m	>40	- <1	<1	0
Copper	ppm	ASTM D5185m		<1	<1	<1
Fin	ppm	ASTM D5185m	>15	0	<1	<1
√anadium	ppm	ASTM D5185m	710	0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES	la la	method	limit/base	current	history1	history2
Boron	nnm	ASTM D5185m	0	<1	<1	<1
Barium	ppm	ASTM D5185m	0	0	0	0
	ppm		60	58		
Molybdenum	ppm	ASTM D5185m			58	57
Manganese	ppm	ASTM D5185m	0	<1	<1	0
Magnesium	ppm	ASTM D5185m	1010	864	889	953
Calcium	ppm	ASTM D5185m	1070	999	1045	1087
Phosphorus	ppm	ASTM D5185m	1150	952	959	982
Zinc	ppm	ASTM D5185m	1270	1135	1183	1261
Sulfur	ppm	ASTM D5185m	2060	2941	2992	3451
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	3	3
Sodium	ppm	ASTM D5185m		0	<1	2
Potassium	ppm	ASTM D5185m	>20	<1	1	2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>4	0.3	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	6.7	7.7	5.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	18.5	18.1
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.3	13.5	13.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.6	8.2	8.9
(1)	09					



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPERTIES		method				history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.6	13.5	13.6	

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10553023 Test Package : FLEET

: GFL0067732 : 05897213

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 13 Jul 2023 Received Diagnosed : 13 Jul 2023

Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GFL Environmental - 820 - Joplin Hauling

3700 West 7th Street Joplin, MO US 64801

Contact: James Jarrett jjarrett@gflenv.com

T: (417)310-2802

Report Id: GFL820 [WUSCAR] 05897213 (Generated: 07/13/2023 16:31:36) Rev: 1

Contact/Location: James Jarrett - GFL820