




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
AUTOCAR 427123

Component
Diesel Engine

Fluid
CHEVRON DELO 400 MULTIGRADE 15W40 (40 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0079531	GFL0076853	---
Sample Date	Client Info	30 Jun 2023	10 Mar 2023	---
Machine Age	hrs	Client Info	3083	2521
Oil Age	hrs	Client Info	3083	2521
Oil Changed	Client Info	Changed	Changed	---
Sample Status		NORMAL	NORMAL	---

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	25	36	---
Chromium	ppm ASTM D5185m >20	1	3	---
Nickel	ppm ASTM D5185m >4	0	<1	---
Titanium	ppm ASTM D5185m	<1	<1	---
Silver	ppm ASTM D5185m >3	0	0	---
Aluminum	ppm ASTM D5185m >20	6	4	---
Lead	ppm ASTM D5185m >40	4	4	---
Copper	ppm ASTM D5185m >330	2	1	---
Tin	ppm ASTM D5185m >15	0	<1	---
Vanadium	ppm ASTM D5185m	0	<1	---
Cadmium	ppm ASTM D5185m	0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	255	252	---
Barium	ppm ASTM D5185m	0	0	---
Molybdenum	ppm ASTM D5185m	127	120	---
Manganese	ppm ASTM D5185m	<1	<1	---
Magnesium	ppm ASTM D5185m	596	628	---
Calcium	ppm ASTM D5185m	1490	1488	---
Phosphorus	ppm ASTM D5185m 1360	686	683	---
Zinc	ppm ASTM D5185m 1480	826	853	---
Sulfur	ppm ASTM D5185m	2669	2318	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	7	12	---
Sodium	ppm ASTM D5185m	<1	8	---
Potassium	ppm ASTM D5185m >20	2	1	---

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	2.5	2.6	---
Nitration	Abs/cm *ASTM D7624 >20	11.3	11.4	---
Sulfation	Abs/.1mm *ASTM D7415 >30	28.9	28.6	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	21.7	20.1	---
Base Number (BN)	mg KOH/g ASTM D2896 12.2	9.4	9.5	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.1	14.9	14.3	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0079531 **Received** : 13 Jul 2023
Lab Number : **05897919** **Diagnosed** : 14 Jul 2023
Unique Number : 10559275 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 409 - Wood Island LF
 E10081 State Hwy M28
 Wetmore, MI
 US 49895
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: