


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**2227007**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0088707</b>	PCA0087245	PCA0076903
Sample Date	Client Info		<b>01 Jul 2023</b>	21 Jan 2023	26 Oct 2022
Machine Age	mls	Client Info	<b>61446</b>	30777	15000
Oil Age	mls	Client Info	<b>0</b>	20000	15000
Oil Changed	Client Info		<b>N/A</b>	Not Changd	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>22</b>	35	39
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >4	<b>2</b>	4	<1
Titanium	ppm	ASTM D5185m	<b>1</b>	4	<1
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m >20	<b>3</b>	7	23
Lead	ppm	ASTM D5185m >40	<b>2</b>	6	7
Copper	ppm	ASTM D5185m >330	<b>49</b>	176	▲ 336
Tin	ppm	ASTM D5185m >15	<b>1</b>	3	5
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>&lt;1</b>	7	164
Barium	ppm	ASTM D5185m 0	<b>2</b>	<1	0
Molybdenum	ppm	ASTM D5185m 50	<b>61</b>	67	122
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	4
Magnesium	ppm	ASTM D5185m 950	<b>872</b>	864	684
Calcium	ppm	ASTM D5185m 1050	<b>1163</b>	1297	1440
Phosphorus	ppm	ASTM D5185m 995	<b>918</b>	894	664
Zinc	ppm	ASTM D5185m 1180	<b>1201</b>	1196	792
Sulfur	ppm	ASTM D5185m 2600	<b>2850</b>	2532	2348

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>4</b>	10	▲ 35
Sodium	ppm	ASTM D5185m	<b>1</b>	1	6
Potassium	ppm	ASTM D5185m >20	<b>9</b>	18	▲ 65



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.4</b>	0.5	0.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.0</b>	9.5	11.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.6</b>	21.5	26

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.6</b>	17.9	25.4
Base Number (BN)	mg KOH/g	ASTM D2896	<b>7.3</b>	6.1	8.2





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.1	10.9

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0088707 **Received** : 14 Jul 2023  
**Lab Number** : 05898307 **Diagnosed** : 17 Jul 2023  
**Unique Number** : 10559663 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**PERDUE FARMS - SALISBURY**  
 7036 ZION CHURCH ROAD  
 SALISBURY, MD  
 US 21802  
 Contact: RICHARD O'NEAL  
 richard.oneal@perdue.com  
 T: (410)543-3628  
 F: (410)341-2164

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)