

OIL ANALYSIS REPORT

Sample Rating Trend





REL133322 Component Transmission (Auto) Fluic

NOT GIVEN (--- GAL)

DIAGNOSIS Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

			H802023	JUI2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0090703	PCA0083083	
Sample Date		Client Info		03 Jul 2023	20 Feb 2023	
Machine Age	hrs	Client Info		27063	26052	
Oil Age	hrs	Client Info		26560	24524	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	ABNORMAL	
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>220	74	61	
Chromium	ppm	ASTM D5185m	>2	0	<1	
Nickel	ppm	ASTM D5185m	>5	<1	0	
Titanium	ppm	ASTM D5185m		<1	<1	
Silver	ppm	ASTM D5185m	>5	0	0	
Aluminum	ppm	ASTM D5185m	>75	26	16	
Lead	ppm	ASTM D5185m	>95	9	6	
Copper	ppm	ASTM D5185m	>60	25	12	
Tin	ppm	ASTM D5185m	>10	2	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		77	84	
Barium	ppm	ASTM D5185m		2	0	
Molybdenum	ppm	ASTM D5185m		<1	<1	
Manganese	ppm	ASTM D5185m		<1	2	
Magnesium	ppm	ASTM D5185m		3	4	
Calcium	ppm	ASTM D5185m		117	111	
Phosphorus	ppm	ASTM D5185m		221	216	
Zinc	ppm	ASTM D5185m		5	24	
Sulfur	ppm	ASTM D5185m		1879	1581	
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	11	8	
Sodium	ppm	ASTM D5185m		3	3	
Potassium	ppm	ASTM D5185m	>20	1	<1	
FLUID DEGRAD	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.24	1.33	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	LIGHT	NONE	
Debris	scalar	*Visual	NONE	NONE	A MODER	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	



OIL ANALYSIS REPORT



	FLUID PROP	PERTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		33.8	34.0	
	SAMPLE IM	AGES	method	limit/base	current	history1	history2
	Color				no image	no image	no image
Jul3/23 -							
	Bottom				no image	no image	no image
	GRAPHS						
	Iron (ppm)			250	Lead (ppm)		
	400			200	Severe		
	300			150			
	200				Abnormal		
				50 0			
	b20/23			Jul3/23	b20/23		Jul3/23
	عمر) Aluminum	n)			۳ Chromium (p	(ma	
	200			6	Severe	F	
	150 - Severe			4			
	Abnormal			E 3	Abnormal		
	50 -			1	-		
	53			0 +			23
	Feb 20,			Jul3	Feb 20		Jul3
	Copper (ppm)			80	Silicon (ppm)		
				60	Severe		
a	80 - Abnormal			Ē.40			
E	40			20	Abnormal		
	20						
	620/23			Jul3/23	b20/23		Jul3/23
	لاً» Viscosity @ 40	°C			ے Acid Number		
	40 38			1.4 @1.2			
	36- 9-24			HOX 1.0			
	0 0 34			10.0 ge			
	30 Abnormal 28 - Abnormal			N 0.4			
	26			0.0			
	Feb 20,			Jul3,	Feb 20,		Jul3/
poratory	: WearCheck USA	- 501 Madi	son Ave., Car	y, NC 27513		UMM - Sho	p 401 - Norton
le No. lumber	: PCA0090703	Receive	d :14J ed ·171	ul 2023 ul 2023		186 South Wa	shington Street
e Number	: 10560092	Diagnos	tician : Wes	Davis			US 02766
Package e report. (: MOB 2 contact Customer Se	ervice at 1-8	300-237-1369			Contact: I Dwilson1@	Dave Wilson Jr. win-waste.com
hods that a	are outside of the ISC	D 17025 sco	ope of accredi	tation.	00000000000		<u>T</u> :
ntormity to spec	inications are based o	n the simple	acceptance d	ecision rule (J	JCGM 106:2012	2)	F: