


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **10690**

Component

Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

568 (GAL)							
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0086153	GFL0083223	GFL0083246	
Sample Date		Client Info		14 Jul 2023	23 Jun 2023	06 Jun 2023	
Machine Age	hrs	Client Info		19114	18982	18829	
Oil Age	hrs	Client Info		1347	633	1062	
Oil Changed		Client Info		Not Changd	Not Changd	Changed	
Sample Status				NORMAL	NORMAL	NORMAL	
WEAR METAI	LS	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>160	91	95	93	
Chromium	ppm	ASTM D5185m	>5	0	0	0	
Nickel	ppm	ASTM D5185m	>5	0	<1	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m	>5	0	0	0	
Aluminum	ppm	ASTM D5185m	>50	7	5	6	
_ead	ppm	ASTM D5185m	>50	<1	2	2	
Copper	ppm	ASTM D5185m	>225	7	8	8	
Tin	ppm	ASTM D5185m	>10	0	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		50	82	78	
Barium	ppm	ASTM D5185m		0	0	0	
Molybdenum	ppm	ASTM D5185m		1	2	<1	
Manganese	ppm	ASTM D5185m		1	<1	<1	
Magnesium	ppm	ASTM D5185m		10	15	1	
Calcium	ppm	ASTM D5185m		141	141	132	
Phosphorus	ppm	ASTM D5185m		238	233	220	
Zinc	ppm	ASTM D5185m		11	27	4	
Sulfur	ppm	ASTM D5185m		2310	1810	1942	
CONTAMINA	NTS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>20	8	8	8	
Sodium	ppm	ASTM D5185m		2	0	0	
Potassium	ppm	ASTM D5185m	>20	2	2	2	
VISUAL		method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	NEG	
FLUID PROPI	ERTIES	method	limit/base	current	history1	history2	
VII 0 4000	- 0:	AOTA DAG	0.4	04.6	04.64	00.0	

Visc @ 40°C

cSt


ASTM D445 34

34.61

33.9




OIL ANALYSIS REPORT




SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image


GRAPHS



Non-ferrous Metals



Viscosity @ 40°C







Laboratory Sample No. Lab Number Unique Number : 10563061 Test Package : FLEET

: GFL0086153 : 05901705

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 18 Jul 2023 Diagnosed : 20 Jul 2023 Diagnostician : Don Baldridge

GFL Environmental - 010 - Stockbridge 1280 Rum Creek Parkway

Stockbridge, GA US 30281

Contact: TECHNICIAN ACCOUNT

wcgfldemo@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL010 [WUSCAR] 05901705 (Generated: 07/20/2023 13:18:42) Rev: 1

Submitted By: TECHNICIAN ACCOUNT

T:

F: