


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
INTERNATIONAL 46

Component
Diesel Engine

Fluid
PHILLIPS 66 Fleet Supreme EC 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0096635	PCA0088228	PCA0076823
Sample Date	Client Info		14 Jun 2023	03 Jan 2023	01 Sep 2022
Machine Age	mls	Client Info	498351	476984	453222
Oil Age	mls	Client Info	21367	23762	25473
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>2.0	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	74	36	68
Chromium	ppm	ASTM D5185m >20	2	2	4
Nickel	ppm	ASTM D5185m >4	0	0	0
Titanium	ppm	ASTM D5185m	<1	<1	3
Silver	ppm	ASTM D5185m >3	0	0	<1
Aluminum	ppm	ASTM D5185m >20	3	3	12
Lead	ppm	ASTM D5185m >40	1	2	6
Copper	ppm	ASTM D5185m >330	1	<1	2
Tin	ppm	ASTM D5185m >15	<1	<1	2
Vanadium	ppm	ASTM D5185m	<1	0	<1
Cadmium	ppm	ASTM D5185m	0	0	<1

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	3	5	26
Barium	ppm	ASTM D5185m	0	0	0
Molybdenum	ppm	ASTM D5185m	66	59	59
Manganese	ppm	ASTM D5185m	1	<1	1
Magnesium	ppm	ASTM D5185m	1018	796	319
Calcium	ppm	ASTM D5185m	1345	1417	1852
Phosphorus	ppm	ASTM D5185m 1116	1128	1073	1006
Zinc	ppm	ASTM D5185m 1250	1355	1287	1229
Sulfur	ppm	ASTM D5185m	3686	2943	3394

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	8	8	13
Sodium	ppm	ASTM D5185m	5	2	3
Potassium	ppm	ASTM D5185m >20	0	2	4



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.6	0.5	0.6
Nitration	Abs/cm	*ASTM D7624 >20	11.0	10.5	13.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.4	22.3	29.5

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	18.0	17.8	24.1
Base Number (BN)	mg KOH/g	ASTM D2896 9.7	7.9	7.4	5.2









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.2	13.9	13.7	14.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0096635 **Received** : 19 Jul 2023
Lab Number : **05902045** **Diagnosed** : 20 Jul 2023
Unique Number : 10563401 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

AREA WIDE TRANSPORTATION
 3085 IL RT 71
 OTTAWA, IL
 US 61350
 Contact: JEFF
 jeff@driveawt.com
 T: (815)587-2947
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)