


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**(89899X) Walgreens**  
Machine Id  
**[Walgreens] 136A69046**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0100191</b>	PCA0094683	PCA0089790
Sample Date	Client Info	<b>02 Aug 2023</b>	20 Apr 2023	06 Jan 2023
Machine Age	mls Client Info	<b>614578</b>	587661	555993
Oil Age	mls Client Info	<b>58585</b>	31668	63796
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>30</b>	17	31
Chromium	ppm ASTM D5185m >5	<b>2</b>	1	2
Nickel	ppm ASTM D5185m >2	<b>0</b>	<1	<1
Titanium	ppm ASTM D5185m	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>14</b>	7	18
Lead	ppm ASTM D5185m >30	<b>0</b>	0	<1
Copper	ppm ASTM D5185m >150	<b>6</b>	6	8
Tin	ppm ASTM D5185m >5	<b>1</b>	<1	1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	<b>1</b>	<1	<1
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 50	<b>70</b>	63	61
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 950	<b>1114</b>	918	937
Calcium	ppm ASTM D5185m 1050	<b>1211</b>	1087	1098
Phosphorus	ppm ASTM D5185m 995	<b>1129</b>	1008	949
Zinc	ppm ASTM D5185m 1180	<b>1443</b>	1233	1237
Sulfur	ppm ASTM D5185m 2600	<b>3488</b>	2603	2709

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>7</b>	5	6
Sodium	ppm ASTM D5185m	<b>2</b>	0	3
Potassium	ppm ASTM D5185m >20	<b>2</b>	2	2



## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.9</b>	0.6	1.1
Nitration	Abs/cm *ASTM D7624 >20	<b>10.7</b>	8.6	10.9
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>24.0</b>	20.6	24.3

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>21.4</b>	17.3	21.5
Base Number (BN)	mg KOH/g ASTM D2896	<b>4.4</b>	6.7	4.5





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.7	11.3

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0100191 **Received** : 08 Aug 2023  
**Lab Number** : 05918369 **Diagnosed** : 09 Aug 2023  
**Unique Number** : 10590283 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1364 - Berkeley-Mt. Vernon**  
 5100 Lake Terrace NE  
 Mt. Vernon, IL  
 US 62864  
 Contact: Erien White  
 ewhite@transervice.com  
 T: (618)244-8726  
 F: (618)244-8791

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)