




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**927058**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0076916</b>	GFL0076922	GFL0055202
Sample Date	Client Info		<b>01 Aug 2023</b>	16 May 2023	07 Feb 2023
Machine Age	hrs	Client Info	<b>13665</b>	13210	12692
Oil Age	hrs	Client Info	<b>456</b>	517	377
Oil Changed	Client Info		<b>Changed</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>6</b>	5	8
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>8</b>	4	6
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>&lt;1</b>	0	1
Lead	ppm	ASTM D5185m >40	<b>2</b>	0	<1
Copper	ppm	ASTM D5185m >330	<b>2</b>	1	2
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>10</b>	14	17
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>62</b>	63	68
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>982</b>	967	916
Calcium	ppm	ASTM D5185m 1070	<b>1142</b>	1103	1120
Phosphorus	ppm	ASTM D5185m 1150	<b>961</b>	990	1021
Zinc	ppm	ASTM D5185m 1270	<b>1220</b>	1239	1222
Sulfur	ppm	ASTM D5185m 2060	<b>3156</b>	3392	3033

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	4	4
Sodium	ppm	ASTM D5185m	<b>10</b>	7	7
Potassium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	3

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.3</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.9</b>	9.4	8.6
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.3</b>	21.1	19.2

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.2</b>	17.6	15.7
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>6.9</b>	7.1	7.9







# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.5	13.7

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0076916 **Received** : 08 Aug 2023  
**Lab Number** : **05919097** **Diagnosed** : 09 Aug 2023  
**Unique Number** : 10591011 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 900 - Antigo HC**  
 1715 Deleglise St.  
 Antigo, WI  
 US 54409  
 Contact: Kirk Koss  
 kirk.koss@gflenv.com  
 T: (715)571-2784  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)