




# PROBLEM SUMMARY

Sample Rating Trend

GLYCOL




Machine Id  
**2488**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (36 QTS)**




## COMPONENT CONDITION SUMMARY

### ▲ Glycol Contamination



### ▲ Viscosity @ 100°C



## RECOMMENDATION

We advise that you check for the source of the coolant leak. Check for low coolant level. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

## PROBLEMATIC TEST RESULTS

Sample Status				ABNORMAL	NORMAL	NORMAL
Sodium	ppm	ASTM D5185m		▲ 201	4	12
Potassium	ppm	ASTM D5185m	>20	▲ 53	3	6
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.2	11.9	13.0

Customer Id: GFL102  
Sample No.: GFL0073305  
Lab Number: 05919642  
Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:  
Jonathan Hester +1 919-379-4092 x4092  
[jhester@wearcheckusa.com](mailto:jhester@wearcheckusa.com)

To change component or sample information:  
Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Change Fluid	---	---	?	Oil and filter change at the time of sampling has been noted.
Change Filter	---	---	?	Oil and filter change at the time of sampling has been noted.
Resample	---	---	?	We recommend an early resample to monitor this condition.
Check Glycol Access	---	---	?	We advise that you check for the source of the coolant leak.

## HISTORICAL DIAGNOSIS

### 25 Apr 2023 Diag: Wes Davis

NORMAL



No corrective action is recommended at this time. Resample at the next service interval to monitor. Metal levels are typical for a new component breaking in. Fuel content negligible. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

[view report](#)



### 08 Sep 2022 Diag: Wes Davis

NORMAL



Resample at the next service interval to monitor. Metal levels are typical for a new component breaking in. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

[view report](#)



### 11 Jul 2022 Diag: Wes Davis

NORMAL



Resample at the next service interval to monitor. Metal levels are typical for a new component breaking in. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

[view report](#)





# OIL ANALYSIS REPORT

Sample Rating Trend

GLYCOL




Machine Id  
**2488**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (36 QTS)**



## DIAGNOSIS

### Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

Sodium and/or potassium levels are high.

### Fluid Condition

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0073305</b>	GFL0073322	GFL0045929
Sample Date	Client Info	<b>07 Aug 2023</b>	25 Apr 2023	08 Sep 2022
Machine Age	hrs	<b>600</b>	600	600
Oil Age	hrs	<b>600</b>	600	414729
Oil Changed	Client Info	<b>Changed</b>	Changed	Changed
Sample Status		<b>ABNORMAL</b>	NORMAL	NORMAL

## WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m >120	<b>6</b>	25	13
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	<1
Nickel	ppm	ASTM D5185m >5	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m >2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>8</b>	2	8
Lead	ppm	ASTM D5185m >40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m >330	<b>2</b>	2	3
Tin	ppm	ASTM D5185m >15	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m 0	<b>33</b>	11	7
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>88</b>	90	60
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>853</b>	820	811
Calcium	ppm	ASTM D5185m 1070	<b>1036</b>	1328	1083
Phosphorus	ppm	ASTM D5185m 1150	<b>924</b>	1044	954
Zinc	ppm	ASTM D5185m 1270	<b>1124</b>	1238	1186
Sulfur	ppm	ASTM D5185m 2060	<b>3520</b>	4053	3044

## CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m >25	<b>7</b>	11	9
Sodium	ppm	ASTM D5185m	<b>▲ 201</b>	4	12
Potassium	ppm	ASTM D5185m >20	<b>▲ 53</b>	3	6
Fuel	%	ASTM D3524 >3.0	<b>&lt;1.0</b>	0.3	<1.0
Glycol	%	*ASTM D2982	<b>NEG</b>	NEG	NEG

## INFRA-RED





method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844 >4	<b>0.1</b>	0.8	1
Nitration	Abs/cm	*ASTM D7624 >20	<b>5.6</b>	10.2	9.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>15.5</b>	21.3	20.7

## FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>10.9</b>	16.8	16.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>9.6</b>	7.0	9.4







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.2	11.9

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0073305 **Received** : 09 Aug 2023  
**Lab Number** : 05919642 **Diagnosed** : 09 Aug 2023  
**Unique Number** : 10591556 **Diagnostician** : Jonathan Hester  
**Test Package** : FLEET ( Additional Tests: FuelDilution, Glycol )

**GFL Environmental - 102 - Morristown TN**  
 415 Ryder Lane, PO Box 1894  
 Morristown, TN  
 US 37813  
 Contact: Ricky Dunlap  
 ricky.dunlap@gflenv.com  
 T: (800)207-6618  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)