




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**731116**

Component  
**Natural Gas Engine**

Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0087219</b>	GFL0087235	GFL0083741
Sample Date	Client Info	<b>03 Aug 2023</b>	07 Jul 2023	08 Jun 2023
Machine Age	hrs	<b>5431</b>	5258	5073
Oil Age	hrs	<b>0</b>	0	1200
Oil Changed	Client Info	<b>Not Chngd</b>	Not Chngd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m >50	<b>45</b>	27	28
Chromium	ppm	ASTM D5185m >4	<b>3</b>	1	2
Nickel	ppm	ASTM D5185m >2	<b>2</b>	<1	1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m >9	<b>5</b>	4	<1
Lead	ppm	ASTM D5185m >30	<b>3</b>	18	17
Copper	ppm	ASTM D5185m >35	<b>1</b>	1	2
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	1	1
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m 50	<b>12</b>	5	4
Barium	ppm	ASTM D5185m 5	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>63</b>	57	65
Manganese	ppm	ASTM D5185m 0	<b>2</b>	1	1
Magnesium	ppm	ASTM D5185m 560	<b>554</b>	596	677
Calcium	ppm	ASTM D5185m 1510	<b>1654</b>	1692	1958
Phosphorus	ppm	ASTM D5185m 780	<b>729</b>	728	816
Zinc	ppm	ASTM D5185m 870	<b>962</b>	984	1092
Sulfur	ppm	ASTM D5185m 2040	<b>2408</b>	2845	3005

## CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m >+100	<b>21</b>	6	9
Sodium	ppm	ASTM D5185m	<b>6</b>	11	5
Potassium	ppm	ASTM D5185m >20	<b>3</b>	5	2

## INFRA-RED



method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	<b>0</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.3</b>	12.0	13.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.7</b>	25.9	29.3

## FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.8</b>	20.9	26.0
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	<b>5.0</b>	3.3	2.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.1	14.6	14.0

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0087219 **Received** : 09 Aug 2023  
**Lab Number** : 05920029 **Diagnosed** : 11 Aug 2023  
**Unique Number** : 10591943 **Diagnostician** : Don Baldrige  
**Test Package** : FLEET

**GFL Environmental - 836 - Kansas City Hauling**  
 7801 East Truman Road  
 Kansas City, MO  
 US 64126  
 Contact: Robert Hart  
 rhart@gflenv.com  
 T: (580)461-1509  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)