



Machine Id 868 Component

OIL

DIAGNOSTICS

Diesel Engine Fluid NOT GIVEN (--- QTS)

COMPONENT CONDITION SUMMARY



▲ Viscosity @ 100°C



RECOMMENDATION

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

PROBLEMATIC TEST RESULTS

Sample Status				ABNORMAL	
Fuel	%	ASTM D3524	>5	<u> </u>	
Visc @ 100°C	cSt	ASTM D445		10.8	

Customer Id: GASMAN Sample No.: PCA0099801 Lab Number: 05923911 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data: Wes Davis +1 905-569-8600 x223 wesd@wearcheck.ca

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

RECOMMENDED ACTIONS							
Action	Status	Date	Done By	Description			
Resample			?	We recommend an early resample to monitor this condition.			
Information Required			?	Please specify the brand, type, and viscosity of the oil on your next sample. Please specify the component make and model with your next sample.			

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 868 Component Diesel Engine Fluid NOT GIVEN (--- QTS)

DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMIFLE INFUR		methou	iinii/base	current	TISTOLAL	TIIStOLY2
Sample Number		Client Info		PCA0099801		
Sample Date		Client Info		20 Jun 2023		
Machine Age	mls	Client Info		95405		
Oil Age	mls	Client Info		7100		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
		and the state	11		In the second second	history O
CONTAMINAT		method	limit/base	current	nistory i	nistory2
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	16		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
		un atta a d	line it /le e e e		la la tanun d	history O
ADDITIVE5		method	limit/base	current	nistory i	nistory2
Boron	ppm	ASTM D5185m		123		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		4		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		18		
Calcium	ppm	ASTM D5185m		1999		
Phosphorus	ppm	ASTM D5185m		886		
Zinc	ppm	ASTM D5185m		1111		
Sulfur						
	ррпі	ASTM D5185m		3849		
CONTAMINAN	TS	ASTM D5185m method	limit/base	3849 current	 history1	 history2
CONTAMINAN Silicon	ppm TS ppm	ASTM D5185m method ASTM D5185m	limit/base	3849 current 5	 history1	 history2
CONTAMINAN Silicon Sodium	ppm TS ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m	limit/base	3849 current 5 2	history1	 history2
CONTAMINAN Silicon Sodium Potassium	ppm TS ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	limit/base >25 >20	3849 current 5 2 6	 history1 	 history2
CONTAMINAN Silicon Sodium Potassium Fuel	ppm TS ppm ppm ppm %	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524	limit/base >25 >20 >5	3849 <u>current</u> 5 2 6 ▲ 5.9	 history1 	 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED	ppm TS ppm ppm %	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method	limit/base >25 >20 >5 limit/base	3849 current 5 2 6 ▲ 5.9 current	 history1 history1	 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm TS ppm ppm %	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method *ASTM D7844	limit/base >25 >20 >5 limit/base >3	3849 current 5 2 6 ▲ 5.9 current 0.4	history1 history1 history1	 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm %	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method *ASTM D7844 *ASTM D7824	limit/base >25 >20 >5 limit/base >3 >20	3849 current 5 2 6 ▲ 5.9 current 0.4 10.4	 history1 history1 	 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % % Abs/cm Abs/1mm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method *ASTM D7844 *ASTM D7624	limit/base >25 >20 >5 limit/base >3 >20 >30	3849 current 5 2 6 ▲ 5.9 current 0.4 10.4 22.7	 history1 history1 	 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % % Abs/cm Abs/1mm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D3524 Method *ASTM D7844 *ASTM D7844 *ASTM D7624	limit/base >25 >20 >5 limit/base >3 >20 >30	3849 current 5 2 6 5.9 current 0.4 10.4 22.7	 history1 history1 	 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation FLUID DEGRAI	ppm ppm ppm % Abs/cm Abs/cm Abs/1mm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 *ASTM D7844 *ASTM D7624 *ASTM D7624 *ASTM D7415	limit/base >25 >20 >5 limit/base >3 >20 >30 limit/base	3849 current 5 2 6 5.9 current 0.4 10.4 22.7 current	 history1 history1 history1	 history2 history2 history2 history2
CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation FLUID DEGRAI	ppm ppm ppm % Abs/cm Abs/.1mm Abs/.1mm	ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 *ASTM D7844 *ASTM D7624 *ASTM D7415 method *ASTM D7414	limit/base >25 >20 >5 limit/base >3 >20 >30 limit/base >25	3849 current 5 2 6 ▲ 5.9 current 0.4 10.4 22.7 current 20.2	history1 history1 history1 history1 history1 history1	 history2 history2 history2 history2



OIL ANALYSIS REPORT



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: TARA MUIRHEAD - GASMAN

114 PA-660

US 16933

T:

F:

history2

history2