

# **OIL ANALYSIS REPORT**

## **Sample Rating Trend**





# KEMP QUARRIES / RIVER VALLEY OZARK WAChine Id WL033

Component
Rear Left Final Drive

MOBIL MOBILTRANS HD 50 (--- GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Moor

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil


## **Fluid Condition**

The condition of the oil is acceptable for the time in service.

S HD 50 ( GAL)		#2010 Jun201	2 Jun2015 Jul2016 Oct20	17 Feb2020 Apr2021 Sep2021 Ju	12022 Jul202	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0069686	PCA0084566	PCA0084667
Sample Date		Client Info		31 Jul 2023	23 May 2023	28 Feb 2023
Machine Age	hrs	Client Info		42005	41725	41433
Oil Age	hrs	Client Info		323556	0	41433
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>800	79	99	73
Chromium	ppm	ASTM D5185m	>10	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m	>15	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>75	2	2	2
Lead	ppm	ASTM D5185m	>10	<1	<1	0
Copper	ppm	ASTM D5185m	>75	4	2	2
Tin	ppm	ASTM D5185m	>8	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		2	2	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		2	2	2
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		22	25	23
Calcium	ppm	ASTM D5185m		2077	2300	2192
Phosphorus	ppm	ASTM D5185m		895	938	830
Zinc	ppm	ASTM D5185m		1061	1174	1043
Sulfur	ppm	ASTM D5185m		4118	5395	4687
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	9	13	8
Sodium	ppm	ASTM D5185m		0	<1	<1
Potassium	ppm	ASTM D5185m	>20	1	<1	0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	195	148	149	152



# **OIL ANALYSIS REPORT**



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

# **GRAPHS** Iron (ppm) Lead (ppm) 1400 25 1200 20 1000 E 15 800 600 400 Aluminum (ppm) Chromium (ppm) 25 20 E 15 Silicon (ppm) Copper (ppm) 100 150 600 틆 100 50 Viscosity @ 40°C Additives 2500 200 2000 cSt (40°C) E 1500 100 500





Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : MOB 1

: PCA0069686 : 05924545 : 10604492

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 14 Aug 2023 : 15 Aug 2023 Diagnostician : Sean Felton

Kemp Quarries - River Valley - Ozark

9446 N Hwy 309 Ozark, AR US 72949

Contact: OZARK NOTIFICATIONS ozark@rivervalleyquarries.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: