


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 420063 Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


J(3)		Nov202	2 Jan2023	May2023 Ar	ug2023	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0083039	GFL0083054	GFL0066567
Sample Date		Client Info		09 Aug 2023	18 May 2023	05 Jan 2023
Machine Age	hrs	Client Info		0	7779	0
Oil Age	hrs	Client Info		0	1042	0
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	33	23	18
Chromium	ppm	ASTM D5185m	>20	1	3	2
Nickel	ppm	ASTM D5185m	>4	0	0	1
Titanium	ppm	ASTM D5185m		0	2	2
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	9	<u>^</u> 26	15
Lead	ppm	ASTM D5185m	>40	15	0	0
Copper	ppm		>330	3	8	7
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m	7.0	0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	18	2	5
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	68	63	58
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	476	930	847
Calcium	ppm	ASTM D5185m	1070	1794	1107	1082
Phosphorus	ppm	ASTM D5185m	1150	1084	1004	953
Zinc	ppm	ASTM D5185m	1270	1312	1199	1178
Sulfur	ppm	ASTM D5185m	2060	3117	3312	2890
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	13	12	5
Sodium	ppm	ASTM D5185m		0	5	2
Potassium	ppm	ASTM D5185m	>20	2	12	12
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	1	0.7	0.4
Nitration	Abs/cm	*ASTM D7624	>20	11.5	9.3	7.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.9	19.2	18.6
FLUID DEGRAI	OATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.7	14.2	14.2
Base Number (BN)	mg KOH/g		9.8	5.8	8.0	8.5
Dage (Marrider (DIV)	my Normy	AO I WI DEUJU	0.0	0.0	0.0	0.0



13

12


OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	RHES	method			history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.8	13.6	13.9

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10604588 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0083039 : 05924641

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Received Diagnosed

: 15 Aug 2023 : 16 Aug 2023 Diagnostician : Sean Felton

GFL Environmental - 072 - Americus - Transwaste

361 McMath Mill Road Americus, GA US 31719

T: (229)924-3669

Contact: RICHARD HEINZERLING richard.heinzerling@gflenv.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)