


OIL ANALYSIS REPORT

Sample Rating Trend









DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The condition of the oil is acceptable for the time in service.

| | | | | Aug2023 | | |
|------------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFOR | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PCA0102189 | | |
| Sample Date | | Client Info | | 11 Aug 2023 | | |
| Machine Age | mls | Client Info | | 50972 | | |
| Oil Age | mls | Client Info | | 0 | | |
| Oil Changed | | Client Info | | Not Changd | | |
| Sample Status | | | | NORMAL | | |
| WEAR METAL | S | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >220 | 63 | | |
| Chromium | ppm | ASTM D5185m | >2 | <1 | | |
| Nickel | ppm | ASTM D5185m | >5 | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | >5 | 0 | | |
| Aluminum | ppm | ASTM D5185m | >75 | 18 | | |
| Lead | ppm | ASTM D5185m | >95 | 6 | | |
| Copper | ppm | ASTM D5185m | >60 | 25 | | |
| Tin | ppm | ASTM D5185m | >10 | 3 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 54 | | |
| Barium | ppm | ASTM D5185m | | 2 | | |
| Molybdenum | ppm | ASTM D5185m | | <1 | | |
| Manganese | ppm | ASTM D5185m | | 2 | | |
| Magnesium | ppm | ASTM D5185m | | 1 | | |
| Calcium | ppm | ASTM D5185m | | 122 | | |
| Phosphorus | ppm | ASTM D5185m | | 204 | | |
| Zinc | ppm | ASTM D5185m | | 4 | | |
| Sulfur | ppm | ASTM D5185m | | 2018 | | |
| CONTAMINAN | TS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 5 | | |
| Sodium | ppm | ASTM D5185m | | 2 | | |
| Potassium | ppm | ASTM D5185m | >20 | 4 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPE | RTIES | method | limit/base | current | history1 | history2 |




OIL ANALYSIS REPORT







GRAPHS



Non-ferrous Metals









Laboratory Sample No. Lab Number Unique Number : 10605635

: PCA0102189 : 05925688 Test Package : FLEET

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 15 Aug 2023 Diagnosed : 17 Aug 2023 Diagnostician : Jonathan Hester

NW WHITE & CO - COLUMBIA DIVISION

100 INDEPENDENCE BLVD COLUMBIA, SC US 29210

Contact: GEORGE EDWARDS

gedwards@nwwhite.com

T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: