


# OIL ANALYSIS REPORT

**Sample Rating Trend**

**NORMAL**

 Machine Id  
**624566**

 Component  
**Diesel Engine**

 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**
**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

**Wear**

All component wear rates are normal.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0093328</b>	PCA0078773	PCA0078814
Sample Date	Client Info			<b>10 Aug 2023</b>	08 Dec 2022	03 Aug 2022
Machine Age	mls	Client Info		<b>96945</b>	61810	49102
Oil Age	mls	Client Info		<b>0</b>	0	0
Oil Changed	Client Info			<b>Not Chngd</b>	Not Chngd	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>15</b>	21	55
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	2	5
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>6</b>	1	<1
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	10	42
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	4	3
Copper	ppm	ASTM D5185m	>330	<b>88</b>	320	278
Tin	ppm	ASTM D5185m	>15	<b>2</b>	3	6
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>5</b>	9	29
Barium	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m	50	<b>57</b>	56	44
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	3
Magnesium	ppm	ASTM D5185m	950	<b>914</b>	866	511
Calcium	ppm	ASTM D5185m	1050	<b>1242</b>	1276	1578
Phosphorus	ppm	ASTM D5185m	995	<b>957</b>	1014	624
Zinc	ppm	ASTM D5185m	1180	<b>1230</b>	1187	786
Sulfur	ppm	ASTM D5185m	2600	<b>3349</b>	3083	1802

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>3</b>	4	8
Sodium	ppm	ASTM D5185m		<b>3</b>	3	8
Potassium	ppm	ASTM D5185m	>20	<b>11</b>	26	107

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.5	1
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.5</b>	9.1	12.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.0</b>	21.0	25.9

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.4</b>	16.6	25.5
Base Number (BN)	mg KOH/g	ASTM D2896		<b>7.6</b>	8.4	7.3









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.5</b>	11.2	10.8

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0093328 **Received** : 16 Aug 2023  
**Lab Number** : 05925720 **Diagnosed** : 16 Aug 2023  
**Unique Number** : 10605667 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #117**  
 2666 LEISCZS BRIDGE RD  
 LEESPORT, PA  
 US 19533  
 Contact: JAMEY RITZ  
 jritz@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: