


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL


Machine Id
PETERBILT 1020
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 40 (--- Oz)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 40. Please confirm.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0083482	---	---
Sample Date	Client Info		20 Jul 2023	---	---
Machine Age	mls	Client Info	0	---	---
Oil Age	mls	Client Info	0	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	---	---
Glycol	WC Method		NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	27	---	---
Chromium	ppm	ASTM D5185m >4	1	---	---
Nickel	ppm	ASTM D5185m >2	<1	---	---
Titanium	ppm	ASTM D5185m	16	---	---
Silver	ppm	ASTM D5185m >2	0	---	---
Aluminum	ppm	ASTM D5185m >25	7	---	---
Lead	ppm	ASTM D5185m >45	<1	---	---
Copper	ppm	ASTM D5185m >85	1	---	---
Tin	ppm	ASTM D5185m >4	<1	---	---
Vanadium	ppm	ASTM D5185m	<1	---	---
Cadmium	ppm	ASTM D5185m	0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	436	---	---
Barium	ppm	ASTM D5185m 10	0	---	---
Molybdenum	ppm	ASTM D5185m 100	73	---	---
Manganese	ppm	ASTM D5185m	<1	---	---
Magnesium	ppm	ASTM D5185m 450	386	---	---
Calcium	ppm	ASTM D5185m 3000	2147	---	---
Phosphorus	ppm	ASTM D5185m 1150	1007	---	---
Zinc	ppm	ASTM D5185m 1350	1196	---	---
Sulfur	ppm	ASTM D5185m 4250	3652	---	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	8	---	---
Sodium	ppm	ASTM D5185m >216	4	---	---
Potassium	ppm	ASTM D5185m >20	2	---	---



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.5	---	---
Nitration	Abs/cm	*ASTM D7624 >20	7.6	---	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	20.7	---	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	15.3	---	---
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	10.3	---	---









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.0	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0083482 **Received** : 16 Aug 2023
Lab Number : 05926665 **Diagnosed** : 17 Aug 2023
Unique Number : 10606612 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

ALBERT HOGOBOOM OILFIELD TRUCKING INC
 767 OIL HILL ROAD
 EL DORADO, KS
 US 67042
 Contact: LOREN JACK
 loren@hogoboom.net
 T:
 F: (316)321-1396

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)