


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



Machine Id 933044

Component

**Transmission (Auto)** 

**PETRO CANADA DuraDrive HD Synthetic** 

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the


### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

| 668 ( LTR)       |        |             |            |             |             |          |
|------------------|--------|-------------|------------|-------------|-------------|----------|
|                  |        |             | Jun2023    | Aug2023     |             |          |
| SAMPLE INFOR     | MATION | method      | limit/base | current     | history1    | history2 |
| Sample Number    |        | Client Info |            | GFL0088764  | GFL0082842  |          |
| Sample Date      |        | Client Info |            | 15 Aug 2023 | 09 Jun 2023 |          |
| Machine Age      | hrs    | Client Info |            | 261         | 35          |          |
| Oil Age          | hrs    | Client Info |            | 261         | 35          |          |
| Oil Changed      |        | Client Info |            | Not Changd  | Not Changd  |          |
| Sample Status    |        |             |            | NORMAL      | NORMAL      |          |
| WEAR METAL       | .S     | method      | limit/base | current     | history1    | history2 |
| Iron             | ppm    | ASTM D5185m | >160       | 32          | 12          |          |
| Chromium         | ppm    | ASTM D5185m | >5         | 0           | <1          |          |
| Nickel           | ppm    | ASTM D5185m | >5         | <1          | 0           |          |
| Titanium         | ppm    | ASTM D5185m |            | 0           | 0           |          |
| Silver           | ppm    | ASTM D5185m | >5         | 0           | 0           |          |
| Aluminum         | ppm    | ASTM D5185m | >50        | 5           | <1          |          |
| Lead             | ppm    | ASTM D5185m | >50        | <1          | 0           |          |
| Copper           | ppm    | ASTM D5185m | >225       | 4           | 1           |          |
| Tin              | ppm    | ASTM D5185m | >10        | <1          | <1          |          |
| Vanadium         | ppm    | ASTM D5185m |            | 0           | 0           |          |
| Cadmium          | ppm    | ASTM D5185m |            | 0           | 0           |          |
| ADDITIVES        |        | method      | limit/base | current     | history1    | history2 |
| Boron            | ppm    | ASTM D5185m |            | 59          | 67          |          |
| Barium           | ppm    | ASTM D5185m |            | 3           | 0           |          |
| Molybdenum       | ppm    | ASTM D5185m |            | <1          | <1          |          |
| Manganese        | ppm    | ASTM D5185m |            | 1           | 1           |          |
| Magnesium        | ppm    | ASTM D5185m |            | <1          | <1          |          |
| Calcium          | ppm    | ASTM D5185m |            | 125         | 125         |          |
| Phosphorus       |        | ASTM D5185m |            | 201         | 222         |          |
| Zinc             | ppm    | ASTM D5185m |            | 18          | 0           |          |
| Sulfur           | ppm    | ASTM D5185m |            | _           | 2107        |          |
|                  | ppm    |             |            | 1787        |             |          |
| CONTAMINAN       | IIS    | method      | limit/base |             | history1    | history2 |
| Silicon          | ppm    | ASTM D5185m | >20        | 5           | 4           |          |
| Sodium           | ppm    | ASTM D5185m |            | 0           | 4           |          |
| Potassium        | ppm    | ASTM D5185m | >20        | 4           | 3           |          |
| VISUAL           |        | method      | limit/base | current     | history1    | history2 |
| White Metal      | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Yellow Metal     | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Precipitate      | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Silt             | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Debris           | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Sand/Dirt        | scalar | *Visual     | NONE       | NONE        | NONE        |          |
| Appearance       | scalar | *Visual     | NORML      | NORML       | NORML       |          |
| Odor             | scalar | *Visual     | NORML      | NORML       | NORML       |          |
| Emulsified Water | scalar | *Visual     | >0.1       | NEG         | NEG         |          |
| Free Water       | scalar | *Visual     |            | NEG         | NEG         |          |
| FLUID PROPE      | RTIES  | method      | limit/base | current     | history1    | history2 |
|                  | 0.     |             |            |             |             |          |




## **OIL ANALYSIS REPORT**







### **GRAPHS**



#### Non-ferrous Metals









Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10607583 Test Package : FLEET

: GFL0088764 : 05927636

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 17 Aug 2023 Diagnosed

: 18 Aug 2023 Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge

1280 Rum Creek Parkway

Stockbridge, GA US 30281

Contact: TECHNICIAN ACCOUNT

wcgfldemo@gmail.com

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) T:

F: