


# **OIL ANALYSIS REPORT**

### Sample Rating Trend



NORMAL



# Machine Id **812090**

Component

**Transmission (Auto)** 

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the

### **Fluid Condition**


The condition of the oil is acceptable for the time in service.

668 ( GAL) Novidez Ouddez Federez Federez Maydez Maydez Maydez Maydez Maydez Auddez							
SAMPLE INFOR	RMATION	<b>Method</b>	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0088750	GFL0086093	GFL0083210	
Sample Date		Client Info		16 Aug 2023	12 Jul 2023	19 Jun 2023	
Machine Age	hrs	Client Info		2394	2203	2008	
Oil Age	hrs	Client Info		2394	2203	2008	
Oil Changed		Client Info		Changed	Not Changd	Not Changd	
Sample Status				NORMAL	NORMAL	NORMAL	
WEAR META	LS	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>160	57	52	50	
Chromium	ppm	ASTM D5185m	>5	0	<1	<1	
Nickel	ppm	ASTM D5185m	>5	0	0	<1	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m	>5	0	0	0	
Aluminum	ppm	ASTM D5185m	>50	27	25	24	
Lead	ppm	ASTM D5185m	>50	6	4	5	
Copper	ppm	ASTM D5185m	>225	18	17	15	
Tin	ppm	ASTM D5185m	>10	5	3	4	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		65	41	68	
Barium	ppm	ASTM D5185m		2	0	0	
Molybdenum	ppm	ASTM D5185m		1	1	1	
Manganese	ppm	ASTM D5185m		1	2	1	
Magnesium	ppm	ASTM D5185m		2	1	1	
Calcium	ppm	ASTM D5185m		108	114	106	
Phosphorus	ppm	ASTM D5185m		206	221	217	
Zinc	ppm	ASTM D5185m		7	0	0	
Sulfur	ppm	ASTM D5185m		1345	1620	1603	
CONTAMINA	NTS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>20	6	5	4	
Sodium	ppm	ASTM D5185m		0	5	6	
Potassium	ppm	ASTM D5185m	>20	4	3	5	
VISUAL		method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG	
Free Water	scalar	*Visual	-	NEG	NEG	NEG	
FLUID PROPI	ERTIE <u>S</u>	method	limit/base	current	history1	history2	

Visc @ 40°C





## **OIL ANALYSIS REPORT**




SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

### **GRAPHS**









Laboratory Sample No. Lab Number Unique Number : 10607586 Test Package : FLEET

: GFL0088750 : 05927639

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 17 Aug 2023 Diagnosed

: 18 Aug 2023 Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge

1280 Rum Creek Parkway Stockbridge, GA US 30281

Contact: JOSHUA TINKER

joshuatinker@gflenv.com T:

Certificate L2367

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: