


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**2145**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0073374</b>	PCA0051917	PCA0051897
Sample Date	Client Info		<b>05 Jun 2023</b>	06 Jul 2022	08 Oct 2021
Machine Age	mls	Client Info	<b>74555</b>	55427	43769
Oil Age	mls	Client Info	<b>19129</b>	11658	28456
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

### CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

### WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>88</b>	64	▲ 108
Chromium	ppm	ASTM D5185m >20	<b>4</b>	3	4
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m >3	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m >20	<b>7</b>	4	7
Lead	ppm	ASTM D5185m >40	<b>1</b>	1	2
Copper	ppm	ASTM D5185m >330	<b>4</b>	3	8
Tin	ppm	ASTM D5185m >15	<b>1</b>	2	2
Antimony	ppm	ASTM D5185m	<b>---</b>	---	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

### ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>0</b>	5	6
Barium	ppm	ASTM D5185m 0	<b>1</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>61</b>	61	58
Manganese	ppm	ASTM D5185m 0	<b>1</b>	1	4
Magnesium	ppm	ASTM D5185m 950	<b>902</b>	905	913
Calcium	ppm	ASTM D5185m 1050	<b>1103</b>	1153	1107
Phosphorus	ppm	ASTM D5185m 995	<b>986</b>	926	974
Zinc	ppm	ASTM D5185m 1180	<b>1188</b>	1154	1177
Sulfur	ppm	ASTM D5185m 2600	<b>2778</b>	3397	2419

### CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>13</b>	7	12
Sodium	ppm	ASTM D5185m	<b>7</b>	8	11
Potassium	ppm	ASTM D5185m >20	<b>2</b>	<1	<1



### INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1.2</b>	1.2	1.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>15.6</b>	15.8	17.4
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>32.3</b>	31.6	37.5

### FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>35.8</b>	35.5	45.8
Base Number (BN)	mg KOH/g	ASTM D2896	<b>3.9</b>	4.9	▲ 2.5





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	12.0	11.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0073374 **Received** : 17 Aug 2023  
**Lab Number** : 05927724 **Diagnosed** : 21 Aug 2023  
**Unique Number** : 10607671 **Diagnostician** : Don Baldrige  
**Test Package** : FLEET

**MIDWEST MOTOR EXPRESS**  
 2169 MUSTANG DR  
 MOUNDS VIEW, MN  
 US 55112  
 Contact: FRANK DIETZ  
 frank.dietz@mmeinc.com  
 T: (763)225-6382  
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)