




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**827019-1031**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0077775</b>	GFL0065062	GFL0065078
Sample Date	Client Info		<b>09 Aug 2023</b>	31 May 2023	20 Feb 2023
Machine Age	hrs	Client Info	<b>14161</b>	14168	13534
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>14</b>	11	5
Chromium	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>2</b>	2	1
Lead	ppm	ASTM D5185m >45	<b>3</b>	4	<1
Copper	ppm	ASTM D5185m >85	<b>&lt;1</b>	1	1
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>4</b>	8	13
Barium	ppm	ASTM D5185m 0	<b>1</b>	2	0
Molybdenum	ppm	ASTM D5185m 60	<b>65</b>	68	59
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	0
Magnesium	ppm	ASTM D5185m 1010	<b>931</b>	918	928
Calcium	ppm	ASTM D5185m 1070	<b>1107</b>	1158	1141
Phosphorus	ppm	ASTM D5185m 1150	<b>1023</b>	1031	1024
Zinc	ppm	ASTM D5185m 1270	<b>1223</b>	1259	1260
Sulfur	ppm	ASTM D5185m 2060	<b>2801</b>	3021	3222

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>13</b>	19	19
Sodium	ppm	ASTM D5185m	<b>9</b>	8	5
Potassium	ppm	ASTM D5185m >20	<b>35</b>	36	6

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.4</b>	0.4	0.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.2</b>	9.6	7.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.2</b>	20.9	18.7

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.7</b>	16.6	14.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.7</b>	7.9	8.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.5	13.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL007775 **Received** : 17 Aug 2023  
**Lab Number** : **05927762** **Diagnosed** : 18 Aug 2023  
**Unique Number** : 10607709 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 650 - West Point Hauling**  
 7825 Parham Landing Road  
 West Point, VA  
 US 23181  
 Contact: Jason Smith  
 jasonsmith@gflenv.com

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)