


OIL ANALYSIS REPORT



Area
KEMP QUARRIES / RIVER VALLEY BACKBONE
Machine Id
WL135
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

Sample Rating Trend



NORMAL

✓

DIAGNOSIS

- Recommendation**
Resample at the next service interval to monitor.
- Wear**
All component wear rates are normal.
- Contamination**
There is no indication of any contamination in the oil.
- Fluid Condition**
The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0084832	PCA0037133	PCA0037193
Sample Date	Client Info		12 Aug 2023	13 Jan 2023	01 Dec 2022
Machine Age	hrs	Client Info	52602	52005	51722
Oil Age	hrs	Client Info	300	300	417
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	ABNORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	18	▲ 118	12
Chromium	ppm	ASTM D5185m >20	<1	3	<1
Nickel	ppm	ASTM D5185m >2	0	▲ 5	0
Titanium	ppm	ASTM D5185m >2	<1	0	0
Silver	ppm	ASTM D5185m >2	<1	0	0
Aluminum	ppm	ASTM D5185m >25	1	▲ 14	<1
Lead	ppm	ASTM D5185m >40	3	1	1
Copper	ppm	ASTM D5185m >330	33	▲ 99	4
Tin	ppm	ASTM D5185m >15	<1	▲ 8	0
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<1	29	0
Barium	ppm	ASTM D5185m 0	0	0	1
Molybdenum	ppm	ASTM D5185m 60	65	95	59
Manganese	ppm	ASTM D5185m 0	<1	5	<1
Magnesium	ppm	ASTM D5185m 1010	978	621	869
Calcium	ppm	ASTM D5185m 1070	1118	1463	1031
Phosphorus	ppm	ASTM D5185m 1150	1015	634	967
Zinc	ppm	ASTM D5185m 1270	1249	810	1180
Sulfur	ppm	ASTM D5185m 2060	3615	1729	3355

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	3	▲ 77	<1
Sodium	ppm	ASTM D5185m	46	4	3
Potassium	ppm	ASTM D5185m >20	11	45	0



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.9	0.9	0.8
Nitration	Abs/cm	*ASTM D7624 >20	6.4	6.2	6.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	18.8	18.8	20.4

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	13.3	13.3	14.5
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	8.3	8.7	9.9









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	14.1	14.3	14.2

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0084832 **Received** : 18 Aug 2023
Lab Number : 05928597 **Diagnosed** : 20 Aug 2023
Unique Number : 10608544 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

Kemp Quarries - River Valley - Backbone
 5600 S Hwy 253
 Huntington, AR
 US 72940
 Contact:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

backbone@rivervalleyquarries.com

T:
F: