




# PROBLEM SUMMARY

Sample Rating Trend



GLYCOL




Machine Id  
**726043-361607**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## COMPONENT CONDITION SUMMARY

### ▲ Glycol Contamination



## RECOMMENDATION

We advise that you check for the source of the coolant leak. Check for low coolant level. We recommend an early resample to monitor this condition.

## PROBLEMATIC TEST RESULTS

Sample Status			ABNORMAL	SEVERE	SEVERE
Sodium	ppm	ASTM D5185m	▲ 167	▲ 872	▲ 576
Potassium	ppm	ASTM D5185m >20	▲ 53	▲ 316	5

Customer Id: GFL865  
Sample No.: GFL0083449  
Lab Number: 05929203  
Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:  
Jonathan Hester +1 919-379-4092 x4092  
[jhester@wearcheckusa.com](mailto:jhester@wearcheckusa.com)

To change component or sample information:  
Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Resample	---	---	?	We recommend an early resample to monitor this condition.
Check Glycol Access	---	---	?	We advise that you check for the source of the coolant leak.

## HISTORICAL DIAGNOSIS

**13 Jun 2023 Diag: Jonathan Hester**

GLYCOL



We advise that you check for the source of the coolant leak. Check for low coolant level. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. Sodium and/or potassium levels are high. Test for glycol is positive. The BN result indicates that there is suitable alkalinity remaining in the oil.

view report



**28 Mar 2023 Diag: Doug Bogart**

GLYCOL



We advise that you check possible coolant leak. Check for low coolant level. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. Sodium and/or potassium levels are high. Test for glycol is negative. The BN result indicates that there is suitable alkalinity remaining in the oil.

view report



**24 Jan 2023 Diag: Jonathan Hester**

GLYCOL



No corrective action is recommended at this time. We recommend an early resample to monitor this condition. All component wear rates are normal. Sodium and/or potassium levels remain high. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


view report





# OIL ANALYSIS REPORT

Sample Rating Trend



GLYCOL



Machine Id  
**726043-361607**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

Sodium and/or potassium levels remain high.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0083449</b>	GFL0083407	GFL0074184
Sample Date	Client Info		<b>09 Aug 2023</b>	13 Jun 2023	28 Mar 2023
Machine Age	hrs	Client Info	<b>18912</b>	18726	18139
Oil Age	hrs	Client Info	<b>18912</b>	18726	0
Oil Changed	Client Info		<b>Not Chngd</b>	Changed	Changed
Sample Status			<b>ABNORMAL</b>	SEVERE	SEVERE

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>7</b>	22	18
Chromium	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >2	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>0</b>	0	2
Lead	ppm	ASTM D5185m >45	<b>0</b>	3	1
Copper	ppm	ASTM D5185m >85	<b>1</b>	2	2
Tin	ppm	ASTM D5185m >4	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>6</b>	0	0
Barium	ppm	ASTM D5185m 0	<b>0</b>	1	0
Molybdenum	ppm	ASTM D5185m 60	<b>70</b>	131	85
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>954</b>	962	989
Calcium	ppm	ASTM D5185m 1070	<b>1163</b>	1075	1185
Phosphorus	ppm	ASTM D5185m 1150	<b>1005</b>	997	1135
Zinc	ppm	ASTM D5185m 1270	<b>1203</b>	1247	1315
Sulfur	ppm	ASTM D5185m 2060	<b>3612</b>	3573	3023

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>4</b>	6	6
Sodium	ppm	ASTM D5185m	<b>▲ 167</b>	▲ 872	▲ 576
Potassium	ppm	ASTM D5185m >20	<b>▲ 53</b>	▲ 316	5
Glycol	%	*ASTM D2982	<b>NEG</b>	◈ 0.12	◈ 0.10

## INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.5</b>	1.1	1
Nitration	Abs/cm	*ASTM D7624 >20	<b>6.6</b>	10.6	9.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.6</b>	22.1	21.5

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>13.9</b>	16.4	15.9
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>9.2</b>	11.3	10.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.3</b>	14.1	14.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0083449 **Received** : 21 Aug 2023  
**Lab Number** : **05929203** **Diagnosed** : 22 Aug 2023  
**Unique Number** : 10609150 **Diagnostician** : Jonathan Hester  
**Test Package** : FLEET

**GFL Environmental - 865 - East Mount Hauling**  
 7213 East Mount Houston Road  
 Houston, TX  
 US 77050  
 Contact: Saul Castillo  
 saul.castillo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)