



# OIL ANALYSIS REPORT

Sample Rating Trend


**NORMAL**



Machine Id  
**927085-260324**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0079280</b>	GFL0067079	GFL0061291
Sample Date	Client Info		<b>09 Aug 2023</b>	22 Feb 2023	11 Jan 2023
Machine Age	hrs	Client Info	<b>17142</b>	15998	15770
Oil Age	hrs	Client Info	<b>600</b>	700	700
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>24</b>	9	36
Chromium	ppm	ASTM D5185m >20	<b>1</b>	0	2
Nickel	ppm	ASTM D5185m >4	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>6</b>	2	5
Lead	ppm	ASTM D5185m >40	<b>0</b>	0	2
Copper	ppm	ASTM D5185m >330	<b>0</b>	<1	1
Tin	ppm	ASTM D5185m >15	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>1</b>	0	2
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	4
Molybdenum	ppm	ASTM D5185m 60	<b>76</b>	57	57
Manganese	ppm	ASTM D5185m 0	<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185m 1010	<b>1167</b>	903	892
Calcium	ppm	ASTM D5185m 1070	<b>1282</b>	1044	1031
Phosphorus	ppm	ASTM D5185m 1150	<b>1228</b>	983	949
Zinc	ppm	ASTM D5185m 1270	<b>1647</b>	1192	1226
Sulfur	ppm	ASTM D5185m 2060	<b>4637</b>	3020	3035

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	2	8
Sodium	ppm	ASTM D5185m	<b>10</b>	6	2
Potassium	ppm	ASTM D5185m >20	<b>0</b>	0	<1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1</b>	0.4	1.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.9</b>	7.3	11.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.3</b>	18.8	20.7

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.0</b>	14.4	15.6
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.7</b>	8.3	9.6







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.1</b>	13.1	13.9

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0079280 **Received** : 21 Aug 2023  
**Lab Number** : **05929321** **Diagnosed** : 21 Aug 2023  
**Unique Number** : 10609268 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 822 - Springfield Hauling**  
 2120 West Bennett Street  
 Springfield, MO  
 US 65807  
 Contact: Dennis Moore  
 dennis.moore@gflenv.com  
 T: (417)403-3641  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)