




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id

**3677**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (34 QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0091179</b>	GFL0076980	GFL0055782
Sample Date	Client Info	<b>17 Aug 2023</b>	22 Jun 2023	02 Sep 2022
Machine Age	hrs	<b>0</b>	0	15044
Oil Age	hrs	<b>600</b>	600	600
Oil Changed	Client Info	<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	<b>7</b>	11	17
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Titanium	ppm ASTM D5185m >2	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	0	<1
Aluminum	ppm ASTM D5185m >15	<b>2</b>	2	3
Lead	ppm ASTM D5185m >25	<b>0</b>	0	<1
Copper	ppm ASTM D5185m >100	<b>&lt;1</b>	<1	4
Tin	ppm ASTM D5185m >4	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>5</b>	6	35
Barium	ppm ASTM D5185m 0	<b>0</b>	0	<1
Molybdenum	ppm ASTM D5185m 60	<b>61</b>	62	46
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>909</b>	1006	583
Calcium	ppm ASTM D5185m 1070	<b>1118</b>	1143	1420
Phosphorus	ppm ASTM D5185m 1150	<b>1022</b>	1088	730
Zinc	ppm ASTM D5185m 1270	<b>1220</b>	1335	904
Sulfur	ppm ASTM D5185m 2060	<b>3385</b>	3855	2309

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	6	20
Sodium	ppm ASTM D5185m	<b>2</b>	10	20
Potassium	ppm ASTM D5185m >20	<b>2</b>	2	0

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	<b>0.3</b>	0.4	1.9
Nitration	Abs/cm *ASTM D7624 >20	<b>5.9</b>	7.1	8.2
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.9</b>	20.2	24.3

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.5</b>	16.5	18.7
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.9</b>	8.3	7.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.4</b>	14.5	14.2

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0091179 **Received** : 21 Aug 2023  
**Lab Number** : **05929379** **Diagnosed** : 22 Aug 2023  
**Unique Number** : 10609326 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 020 - Alamance**  
 703 East Gilbreath St  
 Graham, NC  
 US 27253  
 Contact:  
 richard.belcher@gflenv.com  
 T: (800)207-6618  
 F: (336)229-0526

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)