


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



# Machine Id **2126993**

Component

**Rear Differential** 

GEAR OIL SAE 75W90 (--- QTS)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the


#### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

|                  |        |             |            | Jul2023     |          |          |
|------------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFOR     | MATION | method      | limit/base | current     | history1 | history2 |
| Sample Number    |        | Client Info |            | PCA0101683  |          |          |
| Sample Date      |        | Client Info |            | 16 Jul 2023 |          |          |
| Machine Age      | mls    | Client Info |            | 0           |          |          |
| Oil Age          | mls    | Client Info |            | 0           |          |          |
| Oil Changed      |        | Client Info |            | Not Changd  |          |          |
| Sample Status    |        |             |            | NORMAL      |          |          |
| WEAR METAL       | S      | method      | limit/base | current     | history1 | history2 |
| Iron             | ppm    | ASTM D5185m | >500       | 123         |          |          |
| Chromium         | ppm    | ASTM D5185m | >10        | 2           |          |          |
| Nickel           | ppm    | ASTM D5185m | >10        | 2           |          |          |
| Titanium         | ppm    | ASTM D5185m |            | <1          |          |          |
| Silver           | ppm    | ASTM D5185m |            | 0           |          |          |
| Aluminum         | ppm    | ASTM D5185m | >25        | <1          |          |          |
| Lead             | ppm    | ASTM D5185m | >25        | 0           |          |          |
| Copper           | ppm    | ASTM D5185m | >100       | <1          |          |          |
| Tin              | ppm    | ASTM D5185m | >10        | <1          |          |          |
| Vanadium         | ppm    | ASTM D5185m |            | 0           |          |          |
| Cadmium          | ppm    | ASTM D5185m |            | 0           |          |          |
| ADDITIVES        |        | method      | limit/base | current     | history1 | history2 |
| Boron            | ppm    | ASTM D5185m | 400        | 181         |          |          |
| Barium           | ppm    | ASTM D5185m | 200        | 0           |          |          |
| Molybdenum       | ppm    | ASTM D5185m | 12         | <1          |          |          |
| Manganese        | ppm    | ASTM D5185m |            | 13          |          |          |
| Magnesium        | ppm    | ASTM D5185m | 12         | 4           |          |          |
| Calcium          | ppm    | ASTM D5185m | 150        | 23          |          |          |
| Phosphorus       | ppm    | ASTM D5185m | 1650       | 1117        |          |          |
| Zinc             | ppm    | ASTM D5185m | 125        | 26          |          |          |
| Sulfur           | ppm    | ASTM D5185m | 22500      | 28077       |          |          |
| CONTAMINAN       | ITS    | method      | limit/base | current     | history1 | history2 |
| Silicon          | ppm    | ASTM D5185m | >75        | 31          |          |          |
| Sodium           | ppm    | ASTM D5185m |            | 8           |          |          |
| Potassium        | ppm    | ASTM D5185m | >20        | 5           |          |          |
| VISUAL           |        | method      | limit/base | current     | history1 | history2 |
| White Metal      | scalar | *Visual     | NONE       | NONE        |          |          |
| Yellow Metal     | scalar | *Visual     | NONE       | NONE        |          |          |
| Precipitate      | scalar | *Visual     | NONE       | NONE        |          |          |
| Silt             | scalar | *Visual     | NONE       | NONE        |          |          |
| Debris           | scalar | *Visual     | NONE       | LIGHT       |          |          |
| Sand/Dirt        | scalar | *Visual     | NONE       | NONE        |          |          |
| Appearance       | scalar | *Visual     | NORML      | NORML       |          |          |
| Odor             | scalar | *Visual     | NORML      | NORML       |          |          |
| Emulsified Water | scalar | *Visual     | >.2        | NEG         |          |          |
| Free Water       | scalar | *Visual     |            | NEG         |          |          |
| FLUID PROPE      | RTIES  | method      | limit/base | current     | history1 | history2 |




# **OIL ANALYSIS REPORT**




| SAMPLE IMAGES | method | limit/base | current  | history1 | history2 |
|---------------|--------|------------|----------|----------|----------|
| Color         |        |            | no image | no image | no image |
| Bottom        |        |            | no image | no image | no image |


#### **GRAPHS**



#### Non-ferrous Metals



### Viscosity @ 40°C 135 130







Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10616298

: PCA0101683 : 05931027 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 22 Aug 2023 Diagnosed : 23 Aug 2023 Diagnostician : Don Baldridge

PERDUE FARMS - GEORGETOWN

20621 SAVANAH RD GEORGETOWN, DE US 19947

Contact: ROBERT LOCKWOOD

Robert.Lockwood@Perdue.com T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: