	PROBLEM SUMMARY	Sample Rating Trend	VIS DEBRIS
Machine Id <b>26347</b> Component <b>Rear Differential</b> Fluid <b>GEAR OIL SAE 75W90</b>	( QTS)	Juntatio	
COMPONENT CONDI	TION SUMMARY		

No relevant graphs to display

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

PROBLEMATIC	C TEST	RESULT	S		
Sample Status				ABNORMAL	 
Debris	scalar	*Visual	NONE	A MODER	 

Customer Id: PERGEODE Sample No.: PCA0100161 Lab Number: 05931033 Test Package: FLEET



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Don Baldridge +1 <u>don.b505@comcast.net</u>

*To change component or sample information:* Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u> There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS



## **OIL ANALYSIS REPORT**



Machine Id **26347** Component **Rear Differential** Fluid **GEAR OIL SAE 75W90 (--- QTS)** 

### DIAGNOSIS

#### A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0100161		
Sample Date		Client Info		11 Jun 2023		
Machine Age	mls	Client Info		677011		
	mls	Client Info		677011		
Oil Changed		Client Info		Not Changd		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	60		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
	ppm	ASTM D5185m	>100	<1		
	ppm	ASTM D5185m	>10	0		
	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	400	397		
Barium	ppm	ASTM D5185m	200	0		
Molybdenum	ppm	ASTM D5185m	12	<1		
	ppm	ASTM D5185m		1		
	ppm	ASTM D5185m	12	0		
Calcium	ppm	ASTM D5185m	150	2		
Phosphorus	ppm	ASTM D5185m	1650	1324		
Zinc	ppm	ASTM D5185m	125	4		
Sulfur	ppm	ASTM D5185m	22500	25587		
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	6		
Sodium	ppm	ASTM D5185m		1		
Potassium	ppm	ASTM D5185m	>20	<1		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPER	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	109	87.6		
:23:10) Rev: 1			Contact/I	ocation: ROBE	RT LOCKWOOD	- PERGEODE

Report Id: PERGEODE [WUSCAR] 05931033 (Generated: 08/23/2023 18:23:10) Rev: 1

Contact/Location: ROBERT LOCKWOOD - PERGEODE



Viscosity @ 40°C

# **OIL ANALYSIS REPORT**



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ROBERT LOCKWOOD - PERGEODE

Т:

F: