

OIL ANALYSIS REPORT

Sample Rating Trend





Component Rear Differential Fluid

CHEVRON DELO 400 XLE 10W30 (4 hrs)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The condition of the oil is acceptable for the time in service.

Mayl020 Oct2020 Mar321 Jul2021 Oct2021 Apr/022 Nav/022 Mar3023 Aug0123						
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0102248	PCA0092562	PCA0081230
Sample Date		Client Info		24 Aug 2023	29 Mar 2023	03 Nov 2022
Machine Age	mls	Client Info		224307	175077	175027
Oil Age	mls	Client Info		0	175077	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	64	70	33
Chromium	ppm	ASTM D5185m	>10	<1	0	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	5	5	3
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>100	<1	0	<1
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		279	206	230
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		19	18	18
Manganese	ppm	ASTM D5185m		3	3	2
Magnesium	ppm	ASTM D5185m		90	98	94
Calcium	ppm	ASTM D5185m	2900	201	193	182
Phosphorus	ppm	ASTM D5185m	1100	1344	1250	1196
Zinc	ppm	ASTM D5185m	1200	150	150	139
Sulfur	ppm	ASTM D5185m	4000	23711	25056	24471
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	21	18	12
Sodium	ppm	ASTM D5185m		3	<1	<1
Potassium	ppm	ASTM D5185m	>20	0	<1	0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	MODER	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	81	83.8	84.6	85.7
:07:16) Rev: 1					Submitted E	By: Paul Riddic

Report Id: NWWCOL [WUSCAR] 05936433 (Generated: 08/29/2023 13:07:16) Rev: 1



OIL ANALYSIS REPORT





To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Т:

F: