


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**WIRTGEN 2518 (S/N 1122.0132)**

Component  
**Main Engine**  
Fluid  
**NOT GIVEN (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: Engine Oil )

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0064215</b>	PCA0064218	---
Sample Date	Client Info		<b>25 Aug 2023</b>	23 Aug 2023	---
Machine Age	hrs	Client Info	<b>0</b>	363	---
Oil Age	hrs	Client Info	<b>386</b>	363	---
Oil Changed	Client Info		<b>N/A</b>	N/A	---
Sample Status			<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>4.0	<b>&lt;1.0</b>	<1.0	---
Glycol	WC Method		<b>NEG</b>	NEG	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	<b>7</b>	20	---
Chromium	ppm	ASTM D5185m >8	<b>&lt;1</b>	<1	---
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	---
Titanium	ppm	ASTM D5185m >3	<b>0</b>	0	---
Silver	ppm	ASTM D5185m >2	<b>0</b>	<1	---
Aluminum	ppm	ASTM D5185m >15	<b>2</b>	6	---
Lead	ppm	ASTM D5185m >18	<b>1</b>	4	---
Copper	ppm	ASTM D5185m >80	<b>6</b>	21	---
Tin	ppm	ASTM D5185m >14	<b>&lt;1</b>	2	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>14</b>	39	---
Barium	ppm	ASTM D5185m	<b>2</b>	3	---
Molybdenum	ppm	ASTM D5185m	<b>66</b>	82	---
Manganese	ppm	ASTM D5185m	<b>&lt;1</b>	2	---
Magnesium	ppm	ASTM D5185m	<b>715</b>	208	---
Calcium	ppm	ASTM D5185m	<b>1374</b>	2069	---
Phosphorus	ppm	ASTM D5185m	<b>1058</b>	1049	---
Zinc	ppm	ASTM D5185m	<b>1219</b>	1224	---
Sulfur	ppm	ASTM D5185m	<b>3387</b>	4067	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	<b>10</b>	22	---
Sodium	ppm	ASTM D5185m >75	<b>0</b>	1	---
Potassium	ppm	ASTM D5185m >20	<b>4</b>	12	---



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	<b>0.1</b>	0.2	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>6.0</b>	9.8	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.6</b>	21.1	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.6</b>	18.6	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>8.6</b>	6.5	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	<b>13.9</b>	13.1	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0064215      **Received** : 28 Aug 2023  
**Lab Number** : 05936616      **Diagnosed** : 29 Aug 2023  
**Unique Number** : 10621887      **Diagnostician** : Don Baldrige  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**D-CONSTRUCTION**  
 1488 S BROADWAY  
 COAL CITY, IL  
 US 60416  
 Contact: MICHAEL MCKEE  
 m.mckee@dconstruction.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: