


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**

 Machine Id  
**WIRTGEN 2518 (S/N 1122.0132)**

 Component  
**Main Engine**  
 Fluid  
**NOT GIVEN (--- GAL)**

**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor. ( Customer Sample Comment: Engine Oil )

**Wear**

All component wear rates are normal.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0064218</b>	---	---
Sample Date	Client Info			<b>23 Aug 2023</b>	---	---
Machine Age	hrs	Client Info		<b>363</b>	---	---
Oil Age	hrs	Client Info		<b>363</b>	---	---
Oil Changed	Client Info			<b>N/A</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method		>4.0	<b>&lt;1.0</b>	---	---
Glycol	WC Method			<b>NEG</b>	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>75	<b>20</b>	---	---
Chromium	ppm	ASTM D5185m	>8	<b>&lt;1</b>	---	---
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185m	>3	<b>0</b>	---	---
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	---	---
Aluminum	ppm	ASTM D5185m	>15	<b>6</b>	---	---
Lead	ppm	ASTM D5185m	>18	<b>4</b>	---	---
Copper	ppm	ASTM D5185m	>80	<b>21</b>	---	---
Tin	ppm	ASTM D5185m	>14	<b>2</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---	---
Cadmium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<b>39</b>	---	---
Barium	ppm	ASTM D5185m		<b>3</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>82</b>	---	---
Manganese	ppm	ASTM D5185m		<b>2</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>208</b>	---	---
Calcium	ppm	ASTM D5185m		<b>2069</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>1049</b>	---	---
Zinc	ppm	ASTM D5185m		<b>1224</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>4067</b>	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>22</b>	---	---
Sodium	ppm	ASTM D5185m	>75	<b>1</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>12</b>	---	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		<b>0.2</b>	---	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.8</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.1</b>	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.6</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>6.5</b>	---	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	<b>13.1</b>	---	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0064218 **Received** : 28 Aug 2023  
**Lab Number** : **05936618** **Diagnosed** : 29 Aug 2023  
**Unique Number** : 10621889 **Diagnostician** : Don Baldrige  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**D-CONSTRUCTION**  
 1488 S BROADWAY  
 COAL CITY, IL  
 US 60416  
 Contact: MICHAEL MCKEE  
 m.mckee@dconstruction.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: