




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**426083**

Component  
**Natural Gas Engine**

Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0085371</b>	GFL0085389	GFL0063841
Sample Date	Client Info		<b>23 Aug 2023</b>	23 Jun 2023	22 Mar 2023
Machine Age	hrs	Client Info	<b>20572</b>	20178	19488
Oil Age	hrs	Client Info	<b>0</b>	690	1019
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	<b>9</b>	5	7
Chromium	ppm	ASTM D5185m >4	<b>1</b>	0	<1
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >9	<b>1</b>	0	2
Lead	ppm	ASTM D5185m >30	<b>2</b>	0	1
Copper	ppm	ASTM D5185m >35	<b>2</b>	<1	2
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	<b>8</b>	29	7
Barium	ppm	ASTM D5185m 5	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>55</b>	58	55
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 560	<b>596</b>	616	532
Calcium	ppm	ASTM D5185m 1510	<b>1685</b>	1703	1610
Phosphorus	ppm	ASTM D5185m 780	<b>733</b>	897	718
Zinc	ppm	ASTM D5185m 870	<b>1028</b>	1063	1012
Sulfur	ppm	ASTM D5185m 2040	<b>2929</b>	3040	2457

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	<b>4</b>	3	3
Sodium	ppm	ASTM D5185m	<b>8</b>	3	5
Potassium	ppm	ASTM D5185m >20	<b>4</b>	2	2

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	<b>0</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>11.0</b>	8.0	11.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>22.8</b>	19.5	22.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>19.0</b>	17.4	18.3
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	<b>4.8</b>	7.2	4.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.1	<b>14.9</b>	14.7	14.3

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0085371 **Received** : 29 Aug 2023  
**Lab Number** : **05936930** **Diagnosed** : 29 Aug 2023  
**Unique Number** : 10622201 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 882 - Gainesville**  
 5002 SW 41st Blvd  
 Gainesville, FL  
 US 32608  
 Contact: ROBERT CLARK  
 robert.clark@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: